

# 200CENT SQUARE 250LM FIX TRIMLESS IP20

INDOOR

Fix (not adjustable) 0° - 0°

□ 4.49" x 5.28" - h = 3.54"

Material : CALCYT® plaster



REF N° 200 BLACK

Black






REF N° 200 WHITE

White

## 200CENT SQUARE IP20 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 520 27 530	REF N° 520 27 930	REF N° 520 27 830	REF N° 520 27 730

3W - 250lm - 2 Step MacAdam -  
Serial wiring - □ - ▣  
Requires remote LED driver - 1050mA  
Narrow beam 12° - Ultra lowglare (UGR < 13)




## INSTALLATION KIT

**STANDARD** (included) installation system for ceiling 0.35" - 0.47" - 0.59"

**REF N° 200 99 025** installation system for gypsum ceiling 0.98"

**REF N° 200 99 030** installation system for gypsum ceiling 1.18"




## BEAM ANGLES

**STANDARD** (included) beam angle 12°

# 200CENT SQUARE 500LM FIX TRIMLESS IP20

INDOOR

Fix (not adjustable) 0° - 0°  
 4.49" x 5.28" - h = 3.54"  
 Material : CALCYT® plaster



REF N° 200 BLACK

Black






REF N° 200 WHITE

White

## 200CENT SQUARE IP20 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 520 28 530	REF N° 520 28 930	REF N° 520 28 830	REF N° 520 28 730

5.9W - 500lm - 2 Step MacAdam -  
 Serial wiring -   
 Requires remote LED driver - 700mA  
 Perfect beam 24° - Ultra low glare (UGR < 13)




## INSTALLATION KIT

**STANDARD** (included) installation system for ceiling 0.35" - 0.47" - 0.59"

**REF N° 200 99 025** installation system for gypsum ceiling 0.98"

**REF N° 200 99 030** installation system for gypsum ceiling 1.18"



## BEAM ANGLES

**STANDARD** (included) beam angle 24°

# 200CENT SQUARE 750LM FIX TRIMLESS IP20

INDOOR

Fix (not adjustable) 0° - 0°

4.49" x 5.28" - h = 3.54"

Material : CALCYT® plaster



REF N° 200 BLACK

Black








REF N° 200 WHITE

White

## 200CENT SQUARE IP20 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 520 29 530	REF N° 520 29 930	REF N° 520 29 830	REF N° 520 29 730

6.2W - 750lm - 2 Step MacAdam -  
Serial wiring -  -   
Requires remote LED driver - 250mA  
Standard beam angle 36°




## INSTALLATION KIT

**STANDARD** (included) installation system for ceiling 0.35" - 0.47" - 0.59"

**REF N° 200 99 025** installation system for gypsum ceiling 0.98"

**REF N° 200 99 030** installation system for gypsum ceiling 1.18"



## BEAM ANGLES

**STANDARD** (included) beam angle 36°

