

200CENT SERIES

TWIN ADJUSTABLE RECESSED TRIMLESS

Tiny, powerful, exceptional color? It's possible with the 200Cent Series. At just 1.02" (26 mm), the aperture is the same size as a 2 Euro coin, hence its name. Available in a vast array of options (fixed, adjustable, trimless, trimmed, pendant) the 200Cent series has a fixture for every application.

TECHNICAL DATA

Wattage / Input	2x3W (1050mA), 2x5.9W (700mA), 2x6.2W (250mA)
Power Supply	Remote, not included. See page 2.
Construction	Fixture: Aluminum Body: CALCYT®
CCT	2200K, 2700K, 3000K, 4000K 2400K (6.2W version only)
CRI	>92
Delivered Lumens	562 lm per beam (36°, 6.2W), 438 lm per beam (24°, 5.9W), 212 lm per beam (12°, 3W) All - 3000K
Luminaire Efficacy	91 lm/W per beam (36°, 6.2W), 74 lm/W per beam (24°, 5.9W), 71 lm/W per beam (12°, 3W) All - 3000K
Optics	12° (3W), 24° (5.9W), 36° (6.2W) on Adjustable 0 - 25° Tilt
Finishes	9 Standard. See below and page 3
Cut-Out Dimensions	4.49" x 9.61" x 3.94" h
Fixture Dimensions	Ø1.34" x 3.54"
Aperture	Ø1.02"
LED Source	1 A+ LED
Color Consistency	2-Step MacAdam
IP Rating	IP20

ORDERING INFORMATION

Example: 532 29 520 200 WH GO. Accessories / Power Supplies ordered separately.




Model No.	CCT	Finish (Fixture/Reflector)
532 27 (3W)	520 - 2200K	200 BL CR - Black/Chrome
532 28 (5.9W)	- 2400K (on the 6.2W version)	200 BL BL - Black/Black
532 29 (6.2W)	920 - 2700K	200 BL WH - Black/White
	820 - 3000K	200 BL GO - Black/Gold
	720 - 4000K	200 BL CO - Black/Copper
		200 WH BL - White/Black
		200 WH WH - White/White
		200 WH GO - White/Gold
		200 WH CO - White/Copper

Job Name/Date:

Fixture Type Designation:



Ceiling Cut-Out: 4.49" x 5.28"
Fixture Dimensions



200CENT SERIES

TWIN ADJUSTABLE RECESSED TRIMLESS

SUGGESTED POWER SUPPLIES

1050mA - 3W version (250LM)

Part Number	Description	Input/Output	# of Fixtures
PPLT00466-P	0-10V Dimming to 1.0%	120-277VAC to 1050mA, 10W Class 2	1-2
PPLT00465-P	0-10V Dimming to 1.0%	120-277VAC to 1050mA, 20W Class 2	1-6
PPLT00480-P	0-10V Dimming to 1.0%	120-277VAC to 1050mA, 30W Class 2	1-10
PPLT00309-P	0-10V Dimming to 1.0%	120-277VAC to 1050mA, 50W Class 2	1-16

700mA - 5.9W version (500LM)

Part Number	Description	Input/Output	# of Fixtures
PPLT00466-P	0-10V Dimming to 1.0%	120-277VAC to 700mA, 10W Class 2	1-1
PPLT00470	Phase Dim (120V Only)	120-277VAC to 700mA, 14W Class 2	1-2
PPLT00465-P	0-10V Dimming to 1.0%	120-277VAC to 700mA, 20W Class 2	1-3
PPLT00261	Leading / Trailing-Edge Dimming to 10% (120V only)	120-277VAC to 700mA, 32W Class 2	3-5
PPLT00467-P	0-10V Dimming to 1.0%	120-277VAC to 700mA, 50W Class 2	1-6

Suggested Lutron Compatible - 700mA - 5.9W version (500LM)

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00515	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driv.	120-277VAC to 700mA, 14W, Class 2	1-2
PPLT00517	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driv.	120-277VAC to 700mA, 27W, Class 2	2-4
PPLT00181	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driv.	120-277VAC to 700mA, 38W, Class 2	4-5

250mA - 6.2W version (750LM)

Part Number	Description	Input/Output	# of Fixtures
PPLT00466-P	0-10V Dimming to 1.0%	120-277VAC to 250mA, 10W Class 2, DAMP	1-1
PPLT00290	Leading / Trailing Edge Dimming to 10% (120V Only)	120-277VAC to 250mA, 16W Class 2, DAMP	1-1
PPLT00465-P	0-10V Dimming to 1.0%	120-277VAC to 250mA, 20W Class 2, DAMP	1-2
PPLT00467-P	0-10V Dimming to 1.0%	120-277VAC to 250mA, 50W Class 2, DAMP	1-2

For other power supply options consult factory.

Job Name/Date:

Fixture Type Designation:

200CENT SERIES


TWIN ADJUSTABLE RECESSED TRIMLESS

REQUIRED ACCESSORIES - Installation

STANDARD (included)

Installation System for ceiling 0.35" - 0.47" - 0.59"

PLEASE MENTION CEILING THICKNESS When Ordering for Standard Installation System



200 99 025 (sold separately)
Required Outer Casing
for ceiling 0.98"

200 99 030 (sold separately)
Required Outer Casing
for ceiling 1.18"


FINISHES




PHOTOMETRIC DATA

Note: All photometry is 3000K


Maximum Candela = 2931



Maximum Candela = 1867.5



Maximum Candela = 867.7



Job Name/Date:

Fixture Type Designation: