

200CENT ROUND 250LM W30 FIX TRIMLESS IP20

INDOOR

Fix (not adjustable) Asymmetric 30°

4.49" x 5.28" - h = 4.13"

Material : CALCYT® plaster



REF N° 200 BLACK

Black



REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD




Gold



REF N° 200 COPPER

Copper

200CENT ROUND W30 IP20 250LM CRI 92			
2200°K	2700°K	3000°K	4000°K
REF N° 511 27 530	REF N° 511 27 930	REF N° 511 27 830	REF N° 511 27 730
3W - 250LM - 2-Step MacAdam - Serial wiring -  -  Requires remote LED driver - 1050mA Narrow beam 12° - Ultra low glare (UGR < 13)			



INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 12°

BRICK IN THE WALL/designplan

200CENT ROUND 500LM W30 FIX TRIMLESS IP20

INDOOR

Fix (not adjustable) Asymmetric 30°

4.49" x 5.28" - h = 4.13"

Material : CALCYT® plaster



REF N° 200 BLACK

Black



REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD

Gold






REF N° 200 COPPER

Copper

200CENT ROUND W30 IP20 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N°	REF N°	REF N°	REF N°
511 28 530	511 28 930	511 28 830	511 28 730

5.9W - 500LM - 2-Step MacAdam -
Serial wiring - 
Requires remote LED driver - 700mA
Perfect beam 24° - Ultra low glare (UGR < 13)



INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 24°

BRICK IN THE WALL/designplan

200CENT ROUND 750LM W30 FIX TRIMLESS IP20

INDOOR

Fix (not adjustable) Asymmetric 30°

4.49" x 5.28" - h = 4.13"

Material : CALCYT® plaster



REF N° 200 BLACK

Black



REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD

Gold






REF N° 200 COPPER

Copper

200CENT ROUND W30 IP20 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N°	REF N°	REF N°	REF N°
511 29 530	511 29 930	511 29 830	511 29 730

6.2 W - 750LM - 2-Step MacAdam -
Serial wiring -  - 
Requires remote LED driver - 250mA
Standard beam angle 36°



INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 36°

BRICK IN THE WALL/designplan

