




200CENT ROUND 250LM FIX TRIM IP54

BATHROOM

Fix (not adjustable) 0° - 0°

☐ Ø1.06" - h = 3.74"

Material : Aluminum



REF N° 200 BLACK

Black



200CENT ROUND IP54 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 515 27 531	REF N° 515 27 931	REF N° 515 27 831	REF N° 515 27 731

3W - 250 lm - 2 Step MacAdam -
Serial wiring - ☐ - ☐
Requires remote LED driver - 1050mA
Narrowbeam 12°-Ultralowglare(UGR<13)

REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD

Gold




REF N° 200 COPPER

Copper



INSTALLATION KIT

REF N° 680 01 027 standard hole saw Ø1.06"



BEAM ANGLES

STANDARD (included) beam angle 12°

BRICK IN THE WALL/designplan




200CENT ROUND 500LM FIX TRIM IP54

BATHROOM

Fix (not adjustable) 0° - 0°

□ ∅1.06" - h = 3.74"

Material : Aluminum



REF N° 200 BLACK

Black



REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD

Gold



REF N° 200 COPPER

Copper


200CENT ROUND IP54 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 515 28 531	REF N° 515 28 931	REF N° 515 28 831	REF N° 515 28 731

5.9W - 500 lm - 2 Step MacAdam - Serial wiring - □ - ■
Requires remote LED driver - 700mA
Perfectbeam24°-Ultralowglare(UGR<13)

INSTALLATION KIT

REF N° 680 01 027 standard holesaw ∅1.06"



BEAM ANGLES

STANDARD (included) beam angle 24°

BRICK IN THE WALL/designplan


200CENT ROUND 750LM FIX TRIM IP54

BATHROOM

Fix (not adjustable) 0° - 0°

☞ Ø1.06" - h = 3.74"

Material : Aluminum



REF N° 200 BLACK

Black



REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD



Gold



REF N° 200 COPPER


Copper

200CENT ROUND IP54 750LM CRI 92			
2400°K	2700°K	3000°K	4000°K
REF N° 515 29 531	REF N° 515 29 931	REF N° 515 29 831	REF N° 515 29 731
6.2W - 750 lm - 2 Step MacAdam - Serial wiring - ☐ - ☐ Requires remote LED driver - 250mA Standard beam angle 36°			



INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø1.06"



BEAM ANGLES

STANDARD (included) beam angle 36°

BRICK IN THE WALL/designplan



designplan™ 

designplan/BRICK IN THE WALL