

200CENT ROUND
250LM FIX TRIM IP54

BATHROOM

Fix (not adjustable) 0° - 0°

Ø1.06" - h = 3.74"

Material : Aluminum



REF N° 200 BLACK

Black



REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD




Gold



REF N° 200 COPPER


Copper

200CENT ROUND IP54 250LM CRI 92			
2200°K	2700°K	3000°K	4000°K
REF N°	REF N°	REF N°	REF N°
515 27 531	515 27 931	515 27 831	515 27 731
3W - 250 lm - 2 Step MacAdam - Serial wiring -  -  Requires remote LED driver - 1050mA Narrowbeam12°-Ultralowglare(UGR<13)			



INSTALLATION KIT

REF N° 680 01 027 standard hole saw Ø1.06"



BEAM ANGLES

STANDARD (included) beam angle 12°

BRICK IN THE WALL/designplan

200CENT ROUND
500LM FIX TRIM IP54

BATHROOM

Fix (not adjustable) 0° - 0°

Ø1.06" - h = 3.74"

Material : Aluminum



REF N° 200 BLACK

Black



REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD




Gold



REF N° 200 COPPER


Copper

200CENT ROUND IP54 500LM CRI 92			
2200°K	2700°K	3000°K	4000°K
REF N° 515 28 531	REF N° 515 28 931	REF N° 515 28 831	REF N° 515 28 731
5.9W - 500 lm - 2 Step MacAdam - Serial wiring -  -  Requires remote LED driver - 700mA Perfectbeam24°-Ultralowglare(UGR<13)			



INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø1.06"



BEAM ANGLES

STANDARD (included) beam angle 24°

BRICK IN THE WALL/designplan

200CENT ROUND
750LM FIX TRIM IP54

BATHROOM

Fix (not adjustable) 0° - 0°

Ø1.06" - h = 3.74"

Material : Aluminum



REF N° 200 BLACK

Black



REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD




Gold



REF N° 200 COPPER


Copper

200CENT ROUND IP54 750LM CRI 92			
2400°K	2700°K	3000°K	4000°K
REF N° 515 29 531	REF N° 515 29 931	REF N° 515 29 831	REF N° 515 29 731
6.2W - 750 lm - 2 Step MacAdam - Serial wiring -  -  Requires remote LED driver - 250mA Standard beam angle 36°			



INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø1.06"



BEAM ANGLES

STANDARD (included) beam angle 36°

BRICK IN THE WALL/designplan



designplan® 
designplan/BRICK IN THE WALL