

# 200CENT ROUND 250LM FIX MAXI TRIM IP54

BATHROOM

Fix (not adjustable) 0° - 0°

☐ ⌀1.06" - h = 3.74"

Material : Aluminum



REF N° 200 BLACK

Black






REF N° 200 WHITE

White

## 200CENT ROUND IP54 MAXI TRIM 250LM CRI 92


2200°K	2700°K	3000°K	4000°K
REF N° 516 27 531	REF N° 516 27 931	REF N° 516 27 831	REF N° 516 27 731

3W - 250LM - 2 Step MacAdam -  
Serial wiring - ☐ - ☐  
Requires remote LED driver - 1050mA  
Narrow beam 12° - Ultra low glare (UGR < 13)



## INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø1.06"



## BEAM ANGLES

STANDARD (included) beam angle 12°

# 200CENT ROUND 500LM FIX MAXI TRIM IP54

BATHROOM

Fix (not adjustable) 0° - 0°

☐ Ø1.06" - h = 3.74"

Material : Aluminum



REF N° 200 BLACK

Black






REF N° 200 WHITE

White

## 200CENT ROUND IP54 MAXI TRIM 500LM CRI 92


2200°K	2700°K	3000°K	4000°K
REF N° 516 28 531	REF N° 516 28 931	REF N° 516 28 831	REF N° 516 28 731

5.9 W - 500LM - 2 Step MacAdam -  
Serial wiring - ☐ - ☐  
Requires remote LED driver - 700mA  
Perfectbeam 24° - Ultralowglare (UGR < 13)



## INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø1.06"



## BEAM ANGLES

STANDARD (included) beam angle 24°

# 200CENT ROUND 750LM FIX MAXI TRIM IP54

BATHROOM

Fix (not adjustable) 0° - 0°

☞ Ø1.06" - h = 3.74"

Material : Aluminum



REF N° 200 BLACK

Black






REF N° 200 WHITE

White

## 200CENT ROUND IP54 MAXI TRIM 750LM CRI 92


2400°K	2700°K	3000°K	4000°K
REF N° 516 29 531	REF N° 516 29 931	REF N° 516 29 831	REF N° 516 29 731

6.2 W - 750LM - 2 Step MacAdam -  
Serial wiring - ☐ - ☐  
Requires remote LED driver - 250mA  
Standard beam angle 36°



## INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø1.06"



## BEAM ANGLES

STANDARD (included) beam angle 36°

