

200CENT ROUND 500LM SEMI TRIMLESS IP20

INDOOR

Fix (not adjustable) 0° - 0°

□ 4.49" x 5.28" - h = 2.56"

Material : CALCYT® plaster



200CENT ROUND SEMI IP20 500LM CRI 92




2200°K	2700°K	3000°K	4000°K
REF N° 250 18 520	REF N° 250 18 920	REF N° 250 18 820	REF N° 250 18 720

5.9 W - 500LM - 2-Step MacAdam -

Serial wiring -

Requires remote LED driver - 700mA

Perfect beam 24° - Ultra low glare (UGR < 13)




INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"



BEAM ANGLES

STANDARD (included) beam angle 24°

200CENT ROUND 250LM SEMI TRIMLESS IP20

INDOOR

Fix (not adjustable) 0° - 0°
 □ 4.49" x 5.28" - h = 2.56"
 Material : CALCYT® plaster

REF N° 200 BL CR



Black - Chrome

REF N° 200 BL BL



Black - Black

REF N° 200 WH BL



White - Black

REF N° 200 BL WH



Black - White

REF N° 200 WH WH



White - White

REF N° 200 BL GO



Black - Gold

REF N° 200 WH GO



White - Gold

REF N° 200 BL CO



Black - Copper


REF N° 200 WH CO






White - Copper

200CENT ROUND SEMI IP20 250LM CRI 92


2200°K	2700°K	3000°K	4000°K
REF N° 250 17 520	REF N° 250 17 920	REF N° 250 17 820	REF N° 250 17 720

3W - 250LM - 2-Step MacAdam -
 Serial wiring - 
 Requires remote LED driver - 1050mA
 Narrowbeam 12° - Ultra low glare (UGR < 13)



INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"
REF N° 200 99 025 installation system for gypsum ceiling 0.98"
REF N° 200 99 030 installation system for gypsum ceiling 1.18"




BEAM ANGLES

STANDARD (included) beam angle 12°




200CENT ROUND 750LM SEMI TRIMLESS IP20

INDOOR

Fix (not adjustable) 0° - 0°
 4.49" x 5.28" - h = 2.56"
 Material : CALCYT® plaster




200CENT ROUND SEMI IP20 750LM CRI 92			
2400°K	2700°K	3000°K	4000°K
REF N° 250 19 520	REF N° 250 19 920	REF N° 250 19 820	REF N° 250 19 720
6.2 W - 750LM - 2-Step MacAdam - Serial wiring -  Requires remote LED driver - 250mA Standard beam angle 36°			



INSTALLATION KIT

- STANDARD** (included) installation system for ceiling 0.35" - 0.47" - 0.59"
- REF N° 200 99 025** installation system for gypsum ceiling 0.98"
- REF N° 200 99 030** installation system for gypsum ceiling 1.18"



BEAM ANGLES

STANDARD (included) beam angle 36°

