

200CENT ROUND 250LM SWING 30 TRIMLESS IP20

INDOOR

Adjustable 0° - 27°

4.49" x 5.28" - h = 2.76"

Material : CALCYT® plaster



REF N° 200 BL CR
Black - Chrome



REF N° 200 BL BL
Black - Black



REF N° 200 WH BL
White - Black



REF N° 200 BL WH
Black - White



REF N° 200 WH WH
White - White



REF N° 200 BL GO
Black - Gold



REF N° 200 WH GO
White - Gold






REF N° 200 BL CO
Black - Copper



REF N° 200 WH CO
White - Copper

200CENT ROUND SWING 30 250LM CRI 92			
2200°K	2700°K	3000°K	4000°K
REF N° 551 27 530	REF N° 551 27 930	REF N° 551 27 830	REF N° 551 27 730
3W - 250LM - 2-Step MacAdam - Serial wiring - □ - ■ Requires remote LED driver - 1050mA Narrowbeam 12° - Ultra low glare (UGR < 13)			



INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 12°




200CENT ROUND 500LM SWING 30 TRIMLESS IP20

INDOOR

Adjustable 0° - 27°

4.49" x 5.28" - h = 2.76"

Material : CALCYT® plaster



REF N° 200 BL CR
Black - Chrome



REF N° 200 BL BL
Black - Black



REF N° 200 WH BL
White - Black



REF N° 200 BL WH
Black - White



REF N° 200 WH WH
White - White



REF N° 200 BL GO
Black - Gold



REF N° 200 WH GO
White - Gold



REF N° 200 BL CO
Black - Copper



REF N° 200 WH CO
White - Copper

200CENT ROUND SWING 30 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 551 28 530	REF N° 551 28 930	REF N° 551 28 830	REF N° 551 28 730

5.9W - 500LM - 2-Step MacAdam -

Serial wiring - -

Requires remote LED driver - 700mA

Perfect beam 24° - Ultra low glare (UGR < 13)

INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 24°




200CENT ROUND 750LM SWING 30 TRIMLESS IP20

INDOOR

Adjustable 0° - 27°

4.49" x 5.28" - h = 2.76"

Material : CALCYT® plaster



REF N° 200 BL CR
Black - Chrome



REF N° 200 BL BL
Black - Black



REF N° 200 WH BL
White - Black



REF N° 200 BL WH
Black - White



REF N° 200 WH WH
White - White



REF N° 200 BL GO
Black - Gold



REF N° 200 WH GO
White - Gold



REF N° 200 BL CO
Black - Copper



REF N° 200 WH CO
White - Copper

200CENT ROUND SWING 30 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 551 29 530	REF N° 551 29 930	REF N° 551 29 830	REF N° 551 29 730

6.2W - 750LM - 2-Step MacAdam -
Serial wiring - - -
Requires remote LED driver - 250mA
Standard beam angle 36°

INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"
REF N° 200 99 025 installation system for gypsum ceiling 0.98"
REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 36°

