

200CENT ROUND 250LM SWING 70 TRIMLESS IP20

INDOOR

Adjustable 0° - 68°

4.49" x 5.28" - h = 1.97"

Material : CALCYT® plaster



REF N° 200 BL CR
Black - Chrome



REF N° 200 BL BL
Black - Black



REF N° 200 WH BL
White - Black



REF N° 200 BL WH
Black - White



REF N° 200 WH WH
White - White



REF N° 200 BL GO
Black - Gold



REF N° 200 WH GO
White - Gold





REF N° 200 BL CO
Black - Copper






REF N° 200 WH CO
White - Copper

200CENT ROUND SWING 70 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 550 27 530	REF N° 550 27 930	REF N° 550 27 830	REF N° 550 27 730

3W - 250LM - 2-Step MacAdam -
Serial wiring -  - 
Requires remote LED driver - 1050mA
Narrowbeam 12° - Ultra low glare (UGR < 13)



INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 12°




200CENT ROUND 500LM SWING 70 TRIMLESS IP20

INDOOR

Adjustable 0° - 68°

4.49" x 5.28" - h = 1.97"

Material : CALCYT® plaster



INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 24°

200CENT ROUND SWING 70 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 550 28 530	REF N° 550 28 930	REF N° 550 28 830	REF N° 550 28 730

5.9W - 500LM - 2-Step MacAdam - Serial wiring - □ - ◡

Requires remote LED driver - 700mA

Perfect beam 24° - Ultra low glare (UGR < 13)



REF N° 200 BL CR
Black - Chrome



REF N° 200 BL BL
Black - Black



REF N° 200 WH BL
White - Black



REF N° 200 BL WH
Black - White



REF N° 200 WH WH
White - White



REF N° 200 BL GO
Black - Gold



REF N° 200 WH GO
White - Gold



REF N° 200 BL CO
Black - Copper



REF N° 200 WH CO
White - Copper

200CENT ROUND 750LM SWING 70 TRIMLESS IP20

INDOOR

Adjustable 0° - 68°

4.49" x 5.28" - h = 1.97"

Material : CALCYT® plaster



REF N° 200 BL CR
Black - Chrome



REF N° 200 BL BL
Black - Black



REF N° 200 WH BL
White - Black



REF N° 200 BL WH
Black - White



REF N° 200 WH WH
White - White



REF N° 200 BL GO
Black - Gold



REF N° 200 WH GO
White - Gold



REF N° 200 BL CO
Black - Copper






REF N° 200 WH CO
White - Copper

200CENT ROUND SWING 70 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 550 29 530	REF N° 550 29 930	REF N° 550 29 830	REF N° 550 29 730

6.2W - 750LM - 2-Step MacAdam -
Serial wiring - -
Requires remote LED driver - 250mA
Standard beam angle 36°



INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 36°

BRICK IN THE WALL/designplan

