





200CENT ROUND 250LM SWING 90 TRIM IP20

INDOOR

Adjustable 0° - 90°
 $\varnothing 1.06''$ - h = 2.76''
 Material : Aluminum



REF N° 200 BL CR
Black - Chrome




REF N° 200 BL BL
Black - Black



REF N° 200 WH BL
White - Black

**200CENT ROUND SWING 90
250LM CRI 92**

2200°K	2700°K	3000°K	4000°K
REF N° 553 27 530	REF N° 553 27 930	REF N° 553 27 830	REF N° 553 27 730

3W - 250LM - 2-Step MacAdam -
 Serial wiring -  - 
 Requires remote LED driver - 1050mA
 Narrowbeam 12° - Ultra low glare (UGR < 13)



REF N° 200 BL WH
Black - White



REF N° 200 WH WH
White - White



REF N° 200 BL GO
Black - Gold



REF N° 200 WH GO
White - Gold




REF N° 200 BL CO
Black - Copper



REF N° 200 WH CO
White - Copper

INSTALLATION KIT

REF N° 680 01 027 standard holesaw $\varnothing 1.06''$



BEAM ANGLES

STANDARD (included) beam angle 12°




200CENT ROUND 500LM SWING 90 TRIM IP20

INDOOR

Adjustable 0° - 90°

☞ Ø1.06" - h = 2.76"

Material : Aluminum



200CENT ROUND SWING 90 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 553 28 530	REF N° 553 28 930	REF N° 553 28 830	REF N° 553 28 730

5.9W - 500LM - 2-Step MacAdam -

Serial wiring - ☐ - ☐

Requires remote LED driver - 700mA

Perfect beam 24° - Ultra low glare (UGR < 13)



REF N° 200 BL CR
Black - Chrome



REF N° 200 BL BL
Black - Black



REF N° 200 WH BL
White - Black



REF N° 200 BL WH
Black - White



REF N° 200 WH WH
White - White



REF N° 200 BL GO
Black - Gold



REF N° 200 WH GO
White - Gold




REF N° 200 BL CO
Black - Copper



REF N° 200 WH CO
White - Copper

INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø1.06"



BEAM ANGLES

STANDARD (included) beam angle 24°


200CENT ROUND 750LM SWING 90 TRIM IP20

INDOOR

Adjustable 0° - 90°

☞ Ø1.06" - h = 2.76"

Material : Aluminum



REF N° 200 BL CR
Black - Chrome



REF N° 200 BL BL
Black - Black



REF N° 200 WH BL
White - Black



REF N° 200 BL WH
Black - White



REF N° 200 WH WH
White - White



REF N° 200 BL GO
Black - Gold



REF N° 200 WH GO
White - Gold



REF N° 200 BL CO
Black - Copper





REF N° 200 WH CO
White - Copper

200CENT ROUND SWING 90 750LM CRI 92


2400°K	2700°K	3000°K	4000°K
REF N° 553 29 530	REF N° 553 29 930	REF N° 553 29 830	REF N° 553 29 730

6.2W - 750LM - 2-Step MacAdam -
Serial wiring - ☐ - ☒
Requires remote LED driver - 250mA
Standard beam angle 36°



INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø1.06"



BEAM ANGLES

STANDARD (included) beam angle 36°

