




200CENT ROUND 250LM W50 FIX TRIMLESS IP20

INDOOR

Fix (not adjustable) Asymmetric 50°

□ 4.49" x 5.28" - h = 3.54"

Material : CALCYT® plaster



REF N° 200 BLACK

Black



REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD

Gold



REF N° 200 COPPER

Copper

200CENT ROUND W50 IP20 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 512 27 530	REF N° 512 27 930	REF N° 512 27 830	REF N° 512 27 730

3W - 250LM - 2-Step MacAdam -
Serial wiring - □ - ▴
Requires remote LED driver - 1050mA
Narrow beam 12° - Ultra low glare (UGR < 13)

INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 12°




200CENT ROUND 500LM W50 FIX TRIMLESS IP20

INDOOR

Fix (not adjustable) Asymmetric 50°

□ ▽ 4.49" x 5.28" - h = 3.54"

Material : CALCYT® plaster



REF N° 200 BLACK

Black




REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD

Gold



REF N° 200 COPPER

Copper

200CENT ROUND W50 IP20 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 512 28 530	REF N° 512 28 930	REF N° 512 28 830	REF N° 512 28 730

5.9W - 500LM - 2-Step MacAdam -
Serial wiring - □ - ▽
Requires remote LED driver - 700mA
Perfect beam 24° - Ultra low glare (UGR < 13)

INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 24




200CENT ROUND 750LM W50 FIX TRIMLESS IP20

INDOOR

Fix (not adjustable) Asymmetric 50°

□ 4.49" x 5.28" - h = 3.54"

Material : CALCYT® plaster



REF N° 200 BLACK

Black



REF N° 200 WHITE

White



REF N° 200 CHROME

Chrome



REF N° 200 GOLD

Gold



REF N° 200 COPPER

Copper

200CENT ROUND W50 IP20 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 512 29 530	REF N° 512 29 930	REF N° 512 29 830	REF N° 512 29 730

6.2 W - 750LM - 2-Step MacAdam -
Serial wiring - □ - ▴
Requires remote LED driver - 250mA
Standard beam angle 36°

INSTALLATION KIT

STANDARD (included) installation system for ceiling 0.35" - 0.47" - 0.59"

REF N° 200 99 025 installation system for gypsum ceiling 0.98"

REF N° 200 99 030 installation system for gypsum ceiling 1.18"

BEAM ANGLES

STANDARD (included) beam angle 36°

