

Technical features

IP66	IK09
------	------

Technical data


Wattage	20 WATT
IP Rating	IP66
IK Rating	IK09
Material	High corrosion resistance extruded copper-free aluminum head and extruded pole
Coating	Polyester powder coating with phosphocromating pre-finish
Light Source	NR. 24 x CREE "XH-G" LED
Screws	Stainless steel
Transformer	Electronic power supply 120VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	PG11
Power cable	4.92' power cable included
Gross weight	6.61 lbs



602201P

ALDER 400

Designed by  
NAVA + AROSIO

15.75" height bollard, for outdoor installation, 360° light distribution, phospho-chromatized and polyester powder coated die-cast aluminum head and extruded pole. Tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver 120VAC 50-60Hz, with 24 x CREE "XH-G" LED. IP66 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
mid-power led	 radial 360°	1,600	80.00
<b>4000°K neutral-white</b>			
mid-power led	 radial 360°	1,650	82.50

Finish color options:

 Textured Grey RAL 9006	 Anthracite Grey RAL 7016	 Matte Black (on request)
---	---	---



AC065  
ANCHORAGE UNIT  
FOR ALDER SERIES

