


Alder 400 is a 15.75" bollard for outdoor installation with a radial 360° light distribution with an integral driver. Alder comes in 3 different heights, each available in 2 color temperatures and 3 standard finishes. Dark Sky compliant for output below 80°.



TECHNICAL DATA

Wattage	20W
Power Supply	Integral 120VAC - On / Off 0-10V Dim - <i>Remote Only</i> - Consult Factory
Construction	Head/Pole: Extruded Copper-free Aluminum Lens: Tempered Safety Glass Cable Length: 4.92' included
CCT	3000K, 4000K
BUG Rating	B1-U1-G0
Delivered Lumens	1600 lm (3000K) Dark Sky compliant, output below 80°
Efficacy	80 lm/W
Optics	Radial 360°
Finishes	Textured Gray, Anthracite Gray, Matte Black (on request)
Fixture Dimensions	8.0" head x Ø2.76" base x 15.75" h
Fixture Weight	6.61 lbs
LED Source	24 CREE "XH-G" LED
IP Rating	IP66
IK Rating	IK09

Fixture Dimensions:



ORDERING INFORMATION

Example: 602201P-30K-360-AG. Accessories ordered separately.

602201P	-		-	360	
Model No.	CCT	Optics	Finish		
602201P	30K - 3000K 40K - 4000K	360 - 360°	TG - Textured Gray AG - Anthracite Gray MB - Matte Black (on request)		

Job Name/Date:

Fixture Type Designation:

ACCESSORIES

Installation




AC065
Anchorage Unit

PHOTOMETRIC DATA

Note: All photometry is 3000K

Maximum Candela = 493.3



PHOTOMETRIC FILENAME : ALDER 400 - 602201P 3000K WARMWHITE 20W.IES

Job Name/Date:

Fixture Type Designation: