



The Bell is an indoor and discreet recessed fixture that can be installed on plasterboard walls and ceilings. With a body made of AirCoral®, the backward light source casts a sharp beam which softly scatters the light on the body surface and in the environment.



Ceiling Cut-Out: 8.66" x 8.66"

Fixture Dimensions:  
8.27" l x 8.27" w x 3.94" h



## TECHNICAL DATA

|                           |  |
|---------------------------|--|
| <b>Wattage / Input</b>    | 10W (500mA)                                      |
| <b>Power Supply</b>       | Remote, not included. See page 2.                |
| <b>Construction</b>       | Body: AirCoral®                                  |
| <b>CCT</b>                | 3000K (2700K, 4000K on request, consult factory) |
| <b>CRI</b>                | >90  |
| <b>LED Lumens</b>         | 1,050 lm (3000K)                                 |
| <b>Efficacy</b>           | 105 lm/W (3000K)                                 |
| <b>Optics</b>             | 40° wide beam                                    |
| <b>Finishes</b>           | Unfinished                                       |
| <b>Cut-Out Dimensions</b> | 8.66" x 8.66"                                    |
| <b>Fixture Dimensions</b> | 8.27" l x 8.27" w x 3.94" h                      |
| <b>Aperture</b>           | Ø1.97"   |
| <b>Fixture Weight</b>     | 1.43 lbs   |
| <b>LED Source</b>         | 1 COB Professional LED                           |
| <b>IP Rating</b>          | IP20   |

The body is made of Aircoral® a unique patented composite material that actually purifies the air. It can be calculated how many cubic feet each fixture will purify. See website for Aircoral® calculator.

Additionally, Aircoral® is:

- Antibacterial.
- Antifungal.
- Scratch-resistant.
- Dust-resistant.
- Suitable for painting.
- LEED recognized material.

## ORDERING INFORMATION

Example: BU1901.30.AC.US. Power Supplies ordered separately.

|                  |   |                |    |
|------------------|---|----------------|----|
| BU1901.          | 30  | AC             | US |
| <b>Model No.</b> | <b>CCT</b>  | <b>Finish</b>  |    |
| BU1901.          | 30 - 3000K (standard)<br>27 - 2700K (on request)<br>40 - 4000K (on request) | AC - AirCoral® | US |

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

500mA

| Part Number                 | Description           | Input/Output                       | # of Fixtures |
|-----------------------------|-----------------------|------------------------------------|---------------|
| <a href="#">PPLT00187</a>   | 0-10V Dimming to 10%  | 120-277VAC to 500mA, 10W, Class 2  | 1-1           |
| <a href="#">PPLT00469</a>   | Phase Dim (120V only) | 120VAC to 500mA, 14W, Class 2      | 1-1           |
| <a href="#">PPLT00467-P</a> | 0-10V Dimming to 1%   | 120-277VAC to 500mA, 50W, Class 2  | 1-3           |
| <a href="#">PPLT00538-P</a> | 0-10V Dimming to 0.1% | 120-277VAC to 500mA, 100W, Class 2 | 1-8           |


## Suggested Lutron Compatible

| Part Number               | Option         | Lutron SKU | Dim Range | Description                                    | Input/Output                      | # of Fixtures |
|---------------------------|----------------|------------|-----------|--|-----------------------------------|---------------|
| <a href="#">PPLT00259</a> | L3DAE / L3DA3W | L3DA       | 100%-1%   | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC to 500mA, 10W, Class 2 | 1-1           |
| <a href="#">PPLT00195</a> | L3DAE / L3DA3W | L3DA       | 100%-1%   | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC to 500mA, 19W, Class 2 | 1-1           |
| <a href="#">PPLT00180</a> | L3DAE / L3DA3W | L3DA       | 100%-1%   | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC to 500mA, 27W, Class 2 | 2-2           |

For other power supply options consult factory.

## PHOTOMETRIC DATA

Maximum Candela = 1097



Job Name/Date:

Fixture Type Designation: