



IER AVAIL	ABLE	CODES	
-----------	------	-------	--

BU4423.Z.40.00

40° lens 2700K light color 40° lens light color

Material 4000K (on request)

Weight Mounting IP rating Control gear

Code Туре

Dimensions Cut out for plasterboa Lamp type

Lamp wattage Luminous efficacy Light distribution Fitting Light colour Light hole Voltage connection CRI Note


OPTIONAL

Brick box



79 Trenton Avenue Frenchtown, NJ 08825

Indoor Recessed



TECHNICAL FEATURES

	BU4423.Z.00
	Downlight 90°
	00: Coral®
	2.31 lbs
	Ceiling recessed
	IP40
	Remote constant current electronic driver (not included)
	A: 3.94 in
ard	5.31 imes 5.31 in
	LED 500 mA
	= D Vf: 18 VDC
	$1 \times 9W$
	1 × 1125 lm - 3000K
	Wide beam 40°
	-
	White 3000K
	3.15 × 3.15 in
	By driver (optional)
	>90 Exter white actin place
	Extra white satin glass. Frosted glass recessed
	0.39 in into the ceiling.
	Other available light colours: 2700K, 4000K (on request).

cod. BR4423LT

Tel: (908) 996-7710 Fax: (908) 996-7042




Maxi Bild

0

OTHER AVAILABLE CODES

BU4411.27.00	lens light color	40° 2700K
BU4411.40.00	lens light color	40° 4000K (on request)

TECHNICAL FEATURES				
Code Type	BU4411.00 Downlight 90°			
Material Weight Mounting IP rating	00: Coral® 6.61 lbs Ceiling recessed IP40			
Dimensions Cut out for plasterboard Lamp type	A: 5.31 in 9.45 × 9.45 in LED 700 mA ≇∰			
Lamp wattage Luminous efficacy Light distribution Fitting Light color Light hole Voltage connection CRI Note	1 × 27W 102 lm/W - 3000K Wide beam 40° - White 3000K 6.89 × 6.89 in 50/60Hz >90 Extra white satin glass. Frosted glass recessed 0.39 in . into the ceiling.			
	DALI driver on request. Other available light colors: 2700K, 4000K (on request).			



SQUARE RECESSED FIXTURE 6.89 x 6.89 inch, MINIMALISM AND LIGHTING POWER



* The absorption capacity per ft³ calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 8.86 ft in height and therefore expressed in ft²

Indoor Recessed

