





109001P

BOOK MEDIUM

Square floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver 120-277VAC 50-60Hz, with 8 CREE XP-G2 LED. IP65 rating.



Technical features

IP65 IK08

Technical data

Wattage	12W
IP Rating	IP65
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 8 CREE "XP-G2" LED
Screws	Stainless steel
Transformer	Electronic power supply 120-277VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	Double nickel-plated brass cable gland PG9
Power cable	3.28' neoprene power cable included
Gross weight	5.51 lbs

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
high-power led	10°	1,152	96.00
high-power led	30°	1,095	91.25
high-power led	45°	1,040	86.67
4000°K neutral-white			
high-power led	10°	1,200	100.00
high-power led	30°	1,140	95.00
high-power led	45°	1,083	90.25

Finish color options:

 Textured Grey RAL 9006

 Anthracite Grey RAL 7016

 Matt Black (on request)

SHORT FIXING BRACKET








109002P

BOOK MAXI

Square floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver 120-277VAC 50-60Hz, with 20 CREE XP-G2 LED. IP65 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
high-power led	10°	2,880	96.00
high-power led	30°	2,736	91.20
high-power led	45°	2,600	86.67
4000°K neutral-white			
high-power led	10°	3,000	100.00
high-power led	30°	2,850	95.00
high-power led	45°	2,708	90.26

Finish color options:

 Textured Grey
RAL 9006

 Anthracite Grey
RAL 7016

 Matt Black
(on request)

Technical features

 IP65  IK08


Technical data

Wattage	30W
IP Rating	IP65
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 20 CREE "XP-G2" LED
Screws	Stainless steel
Transformer	Electronic power supply 120-277VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	Double nickel-plated brass cable gland PG9
Power cable	3.28' neoprene power cable included
Gross weight	6.17 lbs

SHORT FIXING BRACKET



MEDIUM FIXING BRACKET



BOTH included in the standard package

