BOULEVARD 02 360



datasheet

Boulevard is a series of outdoor bollards for surface installation. They are available in three different heights with 180° or 360° light emission and 3 standard finishes. Anchorage included.

TECHNICAL DATA

Power Supply Integral Construction Body/Frame: High Corrosion Resistance, Die-cast, Copper-free Aluminum Coating: Polyester Powder Coating with Phosphocromating Pre-finish CCT 3000K, 4000K BUG Rating B0-U2-G1 Delivered Lumens 1600 Im (3000K) Efficacy 84.2 Im/W Optics 360° Finishes Textured Gray, Anthracite Gray, Matte Black Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs IP Rating IP65				
Construction Body/Frame: High Corrosion Resistance, Die-cast, Copper-free Aluminum Coating: Polyester Powder Coating with Phosphocromating Pre-finish CCT 3000K, 4000K BUG Rating B0-U2-G1 Delivered Lumens 1600 Im (3000K) Efficacy 84.2 Im/W Optics 360° Finishes Textured Gray, Anthracite Gray, Matte Black Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs	Wattage / Input	18W (120-277VAC)		
Die-cast, Copper-free Aluminum Coating: Polyester Powder Coating with Phosphocromating Pre-finish CCT 3000K, 4000K BUG Rating B0-U2-G1 Delivered Lumens 1600 Im (3000K) Efficacy 84.2 Im/W Optics 360° Finishes Textured Gray, Anthracite Gray, Matte Black Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs	Power Supply	Integral		
Coating: Polyester Powder Coating with Phosphocromating Pre-finish CCT 3000K, 4000K BUG Rating B0-U2-G1 Delivered Lumens 1600 lm (3000K) Efficacy 84.2 lm/W Optics 360° Finishes Textured Gray, Anthracite Gray, Matte Black Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs	Construction	Body/Frame: High Corrosion Resistance,		
Phosphocromating Pre-finish CCT 3000K, 4000K BUG Rating B0-U2-G1 Delivered Lumens 1600 Im (3000K) Efficacy 84.2 Im/W Optics 360° Finishes Textured Gray, Anthracite Gray, Matte Black Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs		Die-cast, Copper-free Aluminum		
CCT 3000K, 4000K BUG Rating B0-U2-G1 Delivered Lumens 1600 lm (3000K) Efficacy 84.2 lm/W Optics 360° Finishes Textured Gray, Anthracite Gray, Matte Black Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs		Coating: Polyester Powder Coating with		
BUG Rating B0-U2-G1 Delivered Lumens 1600 lm (3000K) Efficacy 84.2 lm/W Optics Finishes Textured Gray, Anthracite Gray, Matte Black Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs		Phosphocromating Pre-finish		
Delivered Lumens 1600 lm (3000K) Efficacy 84.2 lm/W Optics 360° Finishes Textured Gray, Anthracite Gray, Matte Black Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs	ССТ	3000K, 4000K		
Efficacy 84.2 Im/W Optics 360° Finishes Textured Gray, Anthracite Gray, Matte Black Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs	BUG Rating	B0-U2-G1		
Optics 360° Finishes Textured Gray, Anthracite Gray, Matte Black Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs	Delivered Lumens	1600 lm (3000K)		
Finishes Textured Gray, Anthracite Gray, Matte Black Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs	Efficacy	84.2 lm/W		
Fixture Dimensions Ø6.69" x 23.62" h Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs	Optics	360°		
Fixture Weight 12.57 lbs LED Source NR. 12 CREE XH-G mid-power LEDs	Finishes	Textured Gray, Anthracite Gray, Matte Black		
LED Source NR. 12 CREE XH-G mid-power LEDs	Fixture Dimensions	Ø6.69" x 23.62" h		
	Fixture Weight	12.57 lbs		
IP Rating IP65	LED Source	NR. 12 CREE XH-G mid-power LEDs		
	IP Rating	IP65		
Impact Rating IK10	Impact Rating	IK10		




ORDERING INFORMATION

Example: 609004P-30K-360-TG.

609004P	-	- 360	-
Model No.	ССТ	Optics	Finish
609004P	30K - 3000K 40K - 4000K	360 - 360°	TG - Textured Gray AG - Anthracite Gray MB - Matte Black




Fixture Dimensions



PHOTOMETRIC DATA

Note all Photometry is 3000K



Fixture Type Designation:

Job Name/Date:

P: 908-996-7710 F: 908-996-7042

1 of 1