BOULEVARD 03 180



datasheet

Boulevard is a series of outdoor bollards for surface installation. They are available in three different heights with 180° or 360° light emission and 3 standard finishes. Anchorage included.



| Wattage / Input | 9W (120-277VAC) | |
|--------------------|---|--|
| Power Supply | Integral | |
| Construction | Body/Frame: High Corrosion Resistance, | |
| | Die-cast, Copper-free Aluminum | |
| | Coating: Polyester Powder Coating with | |
| | Phosphocromating Pre-finish | |
| ССТ | 3000K, 4000K | |
| Delivered Lumens | 800 lm (3000K) | |
| Efficacy | 88.9 lm/W | |
| Optics | 180° | |
| Finishes | Textured Gray, Anthracite Gray, Matte Black | |
| Fixture Dimensions | Ø6.69" x 39.37" h | |
| Fixture Weight | 15.43 lbs | |
| LED Source | NR. 6 CREE XH-G mid-power LEDs | |
| IP Rating | IP65 | |
| Impact Rating | IK10 | |




ORDERING INFORMATION

Example: 609005P-30K-180-TG.

| 609005P | - | - 180 | - |
|-----------|--|-------------------|---|
| Model No. | ССТ | Optics | Finish |
| 609005P | 30K - 3000K 40K - 4000K | 180 - 180° | TG - Textured Gray AG - Anthracite Gray MB - Matt Black |




Fixture Dimensions



PHOTOMETRIC DATA

Note all Photometry is 3000K



Fixture Type Designation:

Job Name/Date:

P: 908-996-7710 F: 908-996-7042

1 of 1