


Technical features




609001P

BOULEVARD 01 180

Designed by
MOMO DESIGN

8.66" height bollard, round shape, for outdoor surface installation, 180° light emission, phospho-chromatized and polyester powder coated die-cast copper-free aluminum body, polycarbonate diffuser, molded silicone gasket and stainless steel screws. Anchorage bolts included. Built-in LED driver 120-277VAC 50-60Hz, with 12 CREE XH-G mid-power LED. IP65 rating.



Technical data

Wattage	9W
IP Rating	IP65
IK Rating	IK10
Material	High corrosion resistance die-cast copper-free aluminum body and frame.
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 12 CREE XH-G mid-power LED
Screws	Stainless steel
Transformer	Electronic power supply 120-277VAC 50/60Hz built-in
Gasket	Silicone rubber
Diffuser	Polycarbonate diffuser
Anchorage unit included	
Gross weight	8.82 lbs

light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid power led	180°	800	88.88

* Other light colors available on request: Neutral-white

Finish color options:


 Textured Grey
RAL 9006

 Anthracite Grey
RAL 7016

 Matt Black
(on request)



Technical features




609002P

BOULEVARD 01 360

Designed by
MOMO DESIGN

8.66" height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatized and polyester powder coated die-cast copper-free aluminum body, polycarbonate diffuser, molded silicone gasket and stainless steel screws. Anchorage bolts included. Built-in LED driver 120-277VAC 50-60Hz, with 24 CREE XH-G mid-power LED. IP65 rating.



Technical data

Wattage	18W
IP Rating	IP65
IK Rating	IK10
Material	High corrosion resistance die-cast copper-free aluminum body and frame.
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 24 CREE XH-G mid-power LED
Screws	Stainless steel
Transformer	Electronic power supply 120-277VAC 50/60Hz built-in
Gasket	Silicone rubber
Diffuser	Polycarbonate diffuser
	Anchorage unit included
Gross weight	9.26 lbs

light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid power led	360°	1,600	84.21

* Other light colors available on request: Neutral-white

Finish color options:


 Textured Grey
RAL 9006

 Anthracite Grey
RAL 7016

 Matt Black
(on request)



Technical features




609003P

BOULEVARD 02 180

Designed by
MOMO DESIGN

23.62" height bollard, round shape, for outdoor surface installation, 180° light emission, phospho-chromatized and polyester powder coated die-cast copper-free aluminum body, polycarbonate diffuser, molded silicone gasket and stainless steel screws. Anchorage bolts included. Built-in LED driver 120-277VAC 50-60Hz, with 12 CREE XH-G mid-power LED. IP65 rating.



Technical data

Wattage	9W
IP Rating	IP65
IK Rating	IK10
Material	High corrosion resistance die-cast copper-free aluminum body and frame.
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 12 CREE XH-G mid-power LED
Screws	Stainless steel
Transformer	Electronic power supply 120-277VAC 50/60Hz built-in
Gasket	Silicone rubber
Diffuser	Polycarbonate diffuser
Anchorage unit included	
Gross weight	12.13 lbs

light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid power led	180°	800	88.88

* Other light colors available on request: Neutral-white

Finish color options:



Textured Grey RAL 9006

Anthracite Grey RAL 7016

Matt Black (on request)



Technical features




609004P

BOULEVARD 02 360

Designed by
MOMO DESIGN

23.62" height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatized and polyester powder coated die-cast copper-free aluminum body, polycarbonate diffuser, molded silicone gasket and stainless steel screws. Anchorage bolts included. Built-in LED driver 220-240V 50-60Hz, with 24 CREE XH-G mid-power LED. IP65 rating.



Technical data

Wattage	18W
IP Rating	IP65
IK Rating	IK10
Material	High corrosion resistance die-cast copper-free aluminum body and frame.
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 24 CREE XH-G mid-power LED
Screws	Stainless steel
Transformer	Electronic power supply 120-277VAC 50/60Hz built-in
Gasket	Silicone rubber
Diffuser	Polycarbonate diffuser
Anchorage unit included	
Gross weight	12.57 lbs

light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid power led	360°	1,600	84.21

* Other light colors available on request: Neutral-white

Finish color options:

 Textured Grey
RAL 9006

 Anthracite Grey
RAL 7016

 Matt Black
(on request)










609005P

BOULEVARD 03 180

Designed by
MOMO DESIGN

39.37" height bollard, round shape, for outdoor surface installation, 180° light emission, phosphochromatized and polyester powder coated die-cast copper-free aluminum body, polycarbonate diffuser, molded silicone gasket and stainless steel screws. Anchorage bolts included. Built-in LED driver 120-277VAC 50-60Hz, with 12 CREE XH-G mid-power LED. IP65 rating.



Technical features



Technical data

Wattage	9W
IP Rating	IP65
IK Rating	IK10
Material	High corrosion resistance die-cast copper-free aluminum body and frame.
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 12 CREE XH-G mid-power LED
Screws	Stainless steel
Transformer	Electronic power supply 120-277VAC 50/60Hz built-in
Gasket	Silicone rubber
Diffuser	Polycarbonate diffuser
	Anchorage unit included
Gross weight	15.43 lbs



light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid power led	180°	800	88.88

* Other light colors available on request: Neutral-white

Finish color options:

 Textured Grey
RAL 9006

 Anthracite Grey
RAL 7016

 Matt Black
(on request)




609006P

BOULEVARD 03 360

Designed by
MOMO DESIGN

39.37" height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatized and polyester powder coated die-cast copper-free aluminum body, polycarbonate diffuser, molded silicone gasket and stainless steel screws. Anchorage bolts included. Built-in LED driver 120-277VAC 50-60Hz, with 24 CREE XH-G mid-power LED.

IP65 rating.



Technical features



Technical data

Wattage	18W
IP Rating	IP65
IK Rating	IK10
Material	High corrosion resistance die-cast copper-free aluminum body and frame.
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 24 CREE XH-G mid-power LED
Screws	Stainless steel
Transformer	Electronic power supply 120-277VAC 50/60Hz built-in
Gasket	Silicone rubber
Diffuser	Polycarbonate diffuser
Anchorage unit included	
Gross weight	15.87 lbs



light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid power led	360°	1,600	84.21

* Other light colors available on request: Neutral-white

Finish color options:

 Textured Grey
RAL 9006

 Anthracite Grey
RAL 7016

 Matt Black
(on request)