



datasheet


Brick is a wall-mounted, graphic light that highlights outdoor areas essential for public and private life. It is available with a single beam or both an up and down beam, as well as a light strip on the front of the fixture as a marking element. Brick 1 is the single beam version with 3 optics options and 5 standard finishes.


## **TECHNICAL DATA**

Wattage / Input	2.2W (+ 1W Brick 1F with front light)			
Power Supply	Remote 24VDC, not included. See page 2.			
Construction	Body: Anticorodal Aluminum			
	(Anodizing Treatment up to 18 Micron)			
	Lens: Extra Clear Tempered Glass			
	Front Lens: Polished White Milk PMMA (Acrylic)			
	Fixing Bracket/Screws: Stainless Steel			
	Cable Length: 1.64'			
ССТ	3000K, 4000K			
Delivered Lumens	214 lm (Brick 1 - 3000K)			
	214 + 102 lm (Brick 1F - 3000K)			
Efficacy	93.7 lm/W (Brick 1 - 3000K)			
	93.7 + 102 lm/W (Brick 1F - 3000K)			
Optics	3 Standard, See Below			
Finishes	5 Standard, See Below			
Fixture Dimensions	2.76" x 2.36" x 5.91" h			
	(opening on Brick 1F - 4.53" h)			
Color Consistency	<3-Step MacAdam			
IP Rating	IP65			
Impact Resistance	IK07			



**Fixture Dimensions** 





## **ORDERING INFORMATION**

Example: LM02.100107.US.02.MD.BP. Power supplies ordered separately.

			•	•
Model No.	Finish	Optic	ССТ	Front CCT
LM02.100106.US (Brick 1)	<b>01</b> - White	<b>SP</b> - 10-15°	<b>BP</b> - 3000K	RE - Red
LM02.100107.US (Brick 1F)	<b>02</b> - Black	<b>MD</b> - 20-35°	<b>BF</b> - 4000K	<b>GR</b> - Green
	<b>03</b> - Gray	<b>FL</b> - 40-55°		<b>BL</b> - Blue
	<b>04</b> - Cor-ten			NOTE: Front
	11 - Anthracite			light on Brick 1F model only

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042







datasheet

## **SUGGESTED POWER SUPPLIES**

Remote 24VDC Driver in NEMA Enclosure - ELV / TRIAC / 0-10V




Part Number	Description	Input/Output	# of Fixtures
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-34

For other power supply options consult factory.

## PHOTOMETRIC DATA

Note: All photometric data is 3000K



PHOTOMETRIC FILENAME: BRICK 1 LM02.100106.XX.FL.BP.IES

Job Name/Date:

Fixture Type Designation: