


# BRIGHT 3.H

The Bright 3.H is a small, powerful RGBW outdoor recessed fixture. It is available with 3 optics options and can be installed on ceilings, walls or floors. Drive-over rated up to 11,000 lbs with an IP69K protection rating. Not suitable for swimming pools or fountains. **The Bright 3, Smoothy 5 and Litus 5 series all use the same LED.**



Cutout Dimensions for ceiling/wall installations with fixing spring = Ø3.78"

Fixture Dimensions



## TECHNICAL DATA

<b>Wattage / Input</b>	11W (24VDC)
<b>Power Supply</b>	Remote, not included. See page 2.
<b>Construction</b>	Body: Black-Anodized Anticorodal Aluminum Trim: AISI 316L Stainless Steel Lens: Tempered Diffuse Glass Cable Length: 4.92' (standard)
<b>CCT</b>	RGBW
<b>CRI</b>	>80 (4000K)
<b>BUG Rating</b>	B0-U3-G0 (All optics)
<b>Delivered Lumens</b>	278 lm: (R) 43 lm, (G) 87 lm, (B) 32 lm, (W) 116 lm (4000K, 18°)
<b>Efficacy</b>	25.3 lm/W
<b>Optics</b>	18°, 32°, 58°
<b>Finishes</b>	Stainless Steel
<b>Fixture Dimensions</b>	Ø4.41" x 2.95" h
<b>Cut-out Size</b>	Ø3.78" (for ceiling or wall installations)
<b>Fixture Weight</b>	1.76 lbs (with 4.92' standard cable)
<b>LED Source</b>	1 Power RGBW LED Group
<b>Lumen Maintenance</b>	L85, B10 >50,000hrs (Ta 25°C)
<b>Color Consistency</b>	—
<b>Operating Temp.</b>	-4°F to +113°F
<b>IP Rating</b>	IP68, IP69 (Tested to EN / IEC 60598-1)
<b>IK Rating</b>	IK10

## ORDERING INFORMATION

Example: CB3H00000070SI. Accessories / Power Supplies ordered separately.

CB3H00000070		I	-
Model No.	Optics	Finish	Cable Length
CB3H00000070	S - 18° M - 32° L - 58°	I - Stainless Steel	4.92' standard 1 - 16.40'

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

24VDC - RGB

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00288</a>	DMX / RDM (Field Addressable) / Dali	120-277VAC to 24VDC, 100W, Class 2	1-7

For other power supply options consult factory.

## ACCESSORIES

### Installation



**WC0105**  
Outer Casing  
For in-grade use



**WG0400**  
Fixing Spring Ø3.94"  
For ceiling/wall use

## ACCESSORIES

### Controllers (RGBW)



**[PPWD00570](#) - RGBW DMX512+Wifi Controller**

Touch Sensitive  
Can be controlled by WiFi  
Controls 3 zones synchronously and separately


Job Name/Date:

Fixture Type Designation:


## PHOTOMETRIC DATA

Note all Photometry is 3000K


### S - 18°



### M - 32°



### L - 58°



Job Name/Date:

Fixture Type Designation: