


Brom is a line of outdoor wall-mounted luminaires offering a single or double beam and a stainless steel body. It comes in 4 different sizes, white light, and various up or down optics options.

TECHNICAL DATA

Wattage / Input	12W (500mA)
Power Supply	Remote, not included. See page 2.
Construction	Body/Trim: Stainless Steel 316L Lens: Tempered, Transparent Extra-Clear Glass
CCT	2700K, 3000K, 4000K
CRI	>80
BUG Rating	B1-U3-G0 (3000K, 10°, 20°) B0-U3-G0 (3000K, 40°)
Delivered Lumens	251 lm per beam (3000K, 20°)
Efficacy	41.8 lm/W per beam (3000K, 20°)
Optics	12°, 20°, 35° (<i>Up and Down options</i>)
Finishes	Stainless Steel, Custom RAL on request (4 Stage Marine Grade Finish)
Fixture Dimensions	2.76" l x 2.76" w x 5.91" h
Fixture Weight	1.76 lbs
LED Source	6 Power LEDs (3 x 3W)
Lumen Maintenance	L90, B10>50,000hrs (Ta 25°C)
Color Consistency	1/4 ANSI BIN
Operating Temp.	-4°F to 113°F
IP Rating	IP66
Impact Rating	IK08



Fixture Dimensions



ORDERING INFORMATION

Example: BR400625MI. Power supplies ordered separately.

BR40062				
Model No.	CCT	UP Optics	DOWN Optics	Finish
BR40062	F - 2700K 5 - 3000K 9 - 4000K	S - 12° M - 20° L - 35°	S - 12° M - 20° L - 35°	I - Stainless Steel C - Custom RAL (Consult factory for "C")

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

500mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00469	Phase Dim (120V only)	120VAC to 500mA, 14W, Class 2	1-1
PPLT00262	Leading / Trailing-Edge Dimming to 10% (120V only)	120-277VAC to 500mA, 32W, Class 2	2-2
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 500mA, 50W, Class 2	1-2
PPLT00538-P	0-10V Dimming to 0.1%	120-277VAC to 500mA, 100W, Class 2	1-8

Suggested Lutron Compatible Drivers

500mA


Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00195	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC, 19W	1-1
PPLT00180	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC, 27W	2-2

For other power supply options consult factory.


PHOTOMETRIC DATA

Note all Photometry is 3000K


S - 12°



M - 20°



L - 35°



Job Name/Date:

Fixture Type Designation: