

C1-mini-DL is an LED downlight for installation in display case ceilings, suitable for showcase lighting in museum and retail settings. It is 360° rotatable, 55° swivelling and available with a variety of optics, 5 color temperatures and 2 standard finishes.





Euro coin is 0.92"



TECHNICAL DATA

Wattage / Input	2.7W (700mA)
Power Supply	Remote, not included. See page 3.
Dimming	Dimming by Remote Driver - See page 3 <i>(Not Suitable for Dimming Pen)</i>
Construction	Body: Anodized Aluminum
CCT	2700K, 3000K, 3500K, 4000K, 5700K
CRI	>90
Delivered Lumens	150 lm (3000K, 30°)
Efficacy	57 lm/W (3000K, 30°)
Optics	7 Standard, See Below 8° or 15° Glass Lens - Aspherical w/ Diffusion Foil (See Accessories page)
Finishes	2 Standard, See Below Custom RAL
Fixture Dimensions	Ø0.65" x 2.20" h
Lumen Maintenance	L80, B10 >50,000hrs
IP Rating	IP20

Fixture Dimensions



ORDERING INFORMATION

Example: C1-MINI-DL-27-40-18-SI. Accessories / Power Supplies ordered separately.

C1-MINI-DL	-	27	-		-		-	
Model No.	Wattage	CCT	Optics	Finish				
C1-MINI-DL (A400003)	27 - 2.7W	27 - 2700K	18 - 18°	SW - Anodized Black				
		30 - 3000K	26 - 26°	SI - Silver				
		35 - 3500K	30 - 30°	Custom (min. 10)				
		40 - 4000K	45 - 45°	CH - Champagne				
		57 - 5700K	80 - 80°	HA - Hard Anodized				
			47 - 47°+25°	GO - Gold				
			40 - 40°+10°	BR - Mocha Bronze				
				RAL - Custom RAL				

Job Name/Date:

Fixture Type Designation:

ACCESSORIES



Honeycomb Grid
A000601




Anti-Glare Tube
A300003 - ___
SI - silver
SW - black
CH - champagne (min. 10)
HA - hard anodized (min. 10)
GO - gold (min. 10)
BR - mocha bronze (min. 10)
RAL - custom RAL (min. 10)



Inclined Tube
A300146 - ___
SI - silver
SW - black
CH - champagne (min. 10)
HA - hard anodized (min. 10)
GO - gold (min. 10)
BR - mocha bronze (min. 10)



Snoot
A300005 - ___
SI - silver
SW - black
CH - champagne (min. 10)
HA - hard anodized (min. 10)
GO - gold (min. 10)
BR - mocha bronze (min. 10)
RAL - custom RAL (min. 10)



15° Glass Lens
A000500-S
Aspherical with Light Diffusion Foil
and Lens Holder



Barn Door
A300007 - ___
SI - silver
SW - black
RAL - custom RAL (min. 10)



Zoom Optic (9°-33°)
A300138 - ___
SI - silver
SW - black
CH - champagne (min. 10)
HA - hard anodized (min. 10)
GO - gold (min. 10)
BR - mocha bronze (min. 10)

For 8° Optic
Use 15° Glass Lens (A000500-S)
and Snoot (A300005)

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

700mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00498	Phase Dim (120V only)	120VAC to 700mA, 12W, Class 2, DAMP	2-4
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 700mA, 50W, Class 2, DAMP	1-14



Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00515	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 700mA, 14W, Class 2	4-4

For other power supply options consult factory.

PHOTOMETRIC DATA

for light color 3,000K | standard lens 30° | color rendering index typ. 97, R9 > 90, R12 > 90 | color variation ≤ 3 SDCM



Job Name/Date:

Fixture Type Designation: