


C1-mini-S is an LED spotlight for installation in display cases, suitable for showcase lighting in museum and retail settings. It is 360° rotatable, 135° swivelling with screw base or magnetic base and available with a variety of optics, 5 color temperatures and 2 standard finishes.




## TECHNICAL DATA

<b>Wattage / Input</b>	1.8W (600mA)
<b>Power Supply</b>	Remote, not included. See page 2.
<b>Dimming</b>	Dimming by Remote Driver - See page 2 <i>(Not Suitable for Dimming Pen)</i>
<b>Construction</b>	Body: Anodized Aluminum
<b>CCT</b>	2700K, 3000K, 3500K, 4000K, 5700K
<b>CRI</b>	>90
<b>Delivered Lumens</b>	130 lm (3000K, 30°)
<b>Efficacy</b>	72.2 lm/W (3000K, 30°)
<b>Optics</b>	7 Standard, See Below 8° or 15° Glass Lens - Aspherical w/ Diffusion Foil (See Accessories page)
<b>Finishes</b>	2 Standard, See Below Custom RAL
<b>Fixture Dimensions</b>	Ø0.55" x 0.71" (head) Ø0.39" x 0.79" (magnetic base) Ø0.39" x 0.75" (screw base)
<b>Lumen Maintenance</b>	L80, B10 >50,000hrs
<b>IP Rating</b>	IP20


### Fixture Dimensions



magnetic base



screw base



## ORDERING INFORMATION

Example: C1-MINI-S-18-40-18-SI-M. Accessories / Power Supplies ordered separately.

C1-MINI-S	-	18	-		-		-		-	
Model No.	Wattage	CCT	Optics	Finish	Base					
C1-MINI-S (A400012)	18 - 1.8W	27 - 2700K	18 - 18°	SW - Anodized Black	M - Magnetic S - Screw					
		30 - 3000K	26 - 26°	SI - Silver						
		35 - 3500K	30 - 30°	Custom (min. 10)						
		40 - 4000K	45 - 45°	CH - Champagne						
		57 - 5700K	80 - 80°	HA - Hard Anodized						
		47 - 47°+25°	40 - 40°+10°	GO - Gold						
				BR - Mocha Bronze						
				RAL - Custom RAL						


Job Name/Date:

Fixture Type Designation:

## ACCESSORIES



**Honeycomb Grid**  
A000600



**\*15° Glass Lens**  
A000500-S  
Aspherical with Light Diffusion Foil  
and Lens Holder

**For 8° Optic**  
Use 15° Glass Lens (A000500-S)  
and Snoot (A300005)



**Anti-Glare Tube**  
A300016 - \_\_  
SI - silver  
SW - black  
CH - champagne (min. 10)  
HA - hard anodized (min. 10)  
GO - gold (min. 10)  
BR - mocha bronze (min. 10)  
RAL - custom RAL (min. 10)



**Inclined Tube**  
A300019 - \_\_  
SI - silver  
SW - black  
CH - champagne (min. 10)  
HA - hard anodized (min. 10)  
GO - gold (min. 10)  
BR - mocha bronze (min. 10)



**Barn Door**  
A300020 - \_\_  
SI - silver  
SW - black  
RAL - custom RAL (min. 10)

## SUGGESTED POWER SUPPLIES

600mA

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00309-P</a>	0-10V Dimming to 0.1%	120-277VAC to 600mA, 50W, Class 2, DAMP	1-16




For other power supply options consult factory.

Job Name/Date:

Fixture Type Designation:

## PHOTOMETRIC DATA

for light color ~3,000 K | standard lens 30° | color rendering index typ. 97, R9 > 90, R12 > 90 | color variation ≤ 3 SDCM



Job Name/Date:

Fixture Type Designation: