CASE MAXI RGBW

Case is a family of square outdoor floodlights for installation on a façade or wall. Case Maxi RGBW is a color changing version of the largest size offered in 3 optics options and 3 standard finishes.

TECHNICAL DATA


Wattage / Input28W (24VDC)Power SupplyRemote driver with DMX integrated into fixture See page 2 for remote power suppliesConstructionBody/Bracket: High Corrosion Resistance, Die-cast, Copper-free Aluminum Lens: Tempered Safely Glass Cable Length: 3.28'CCTRGBWDelivered Lumens992 lm (25°)Efficacy35.4 lm/WOptics12°, 25°, 35°Finishes9.61" l x 5.04" w x 14.88" hFixture Dimensions9.61" l x 5.04" w x 14.88" hFixture Weight11.02 lbsLED Source6 CREE "XML" COLOR RGBW LEDImpact RatingIK08			
Power SupplySee page 2 for remote power suppliesConstructionBody/Bracket: High Corrosion Resistance, Die-cast, Copper-free Aluminum Lens: Tempered Safely Glass Cable Length: 3.28'CCTRGBWDelivered Lumens992 lm (25°)Efficacy35.4 lm/WOptics12°, 25°, 35°FinishesTextured Gray, Anthractie Gray, Matte BlackFixture Dimensions9.61" l x 5.04" w x 14.88" hFixture Weight11.02 lbsLED Source6 CREE "XML" COLOR RGBW LEDIP RatingIP65	Wattage / Input	28W (24VDC)	
Die-cast, Copper-free Aluminum Lens: Tempered Safely Glass Cable Length: 3.28'CCTRGBWDelivered Lumens992 lm (25°)Efficacy35.4 lm/WOptics12°, 25°, 35°FinishesTextured Gray, Anthractie Gray, Matte BlackFixture Dimensions9.61" l x 5.04" w x 14.88" hFixture Weight11.02 lbsLED Source6 CREE "XML" COLOR RGBW LEDIP RatingIP65	Power Supply	0	
Delivered Lumens992 lm (25°)Efficacy35.4 lm/WOptics12°, 25°, 35°FinishesTextured Gray, Anthractie Gray, Matte BlackFixture Dimensions9.61" l x 5.04" w x 14.88" hFixture Weight11.02 lbsLED Source6 CREE "XML" COLOR RGBW LEDIP RatingIP65	Construction	Die-cast, Copper-free Aluminum Lens: Tempered Safely Glass	
Efficacy35.4 lm/WOptics12°, 25°, 35°FinishesTextured Gray, Anthractie Gray, Matte BlackFixture Dimensions9.61" l x 5.04" w x 14.88" hFixture Weight11.02 lbsLED Source6 CREE "XML" COLOR RGBW LEDIP RatingIP65	ССТ	RGBW	
Optics12°, 25°, 35°FinishesTextured Gray, Anthractie Gray, Matte BlackFixture Dimensions9.61" I x 5.04" w x 14.88" hFixture Weight11.02 lbsLED Source6 CREE "XML" COLOR RGBW LEDIP RatingIP65	Delivered Lumens	992 lm (25°)	
FinishesTextured Gray, Anthractie Gray, Matte BlackFixture Dimensions9.61" l x 5.04" w x 14.88" hFixture Weight11.02 lbsLED Source6 CREE "XML" COLOR RGBW LEDIP RatingIP65	Efficacy	35.4 lm/W	
Fixture Dimensions9.61" I x 5.04" w x 14.88" hFixture Weight11.02 lbsLED Source6 CREE "XML" COLOR RGBW LEDIP RatingIP65	Optics	12°, 25°, 35°	
Fixture Weight 11.02 lbs LED Source 6 CREE "XML" COLOR RGBW LED IP Rating IP65	Finishes	Textured Gray, Anthractie Gray, Matte Black	
LED Source 6 CREE "XML" COLOR RGBW LED IP Rating IP65	Fixture Dimensions	9.61" l x 5.04" w x 14.88" h	
IP Rating IP65	Fixture Weight	11.02 lbs	
	LED Source	6 CREE "XML" COLOR RGBW LED	
Impact Rating IK08	IP Rating	IP65	
	Impact Rating	IK08	

designplan@

datasheet



Fixture Dimensions



ORDERING INFORMATION

Example: 101008RG	BWP-25-TG.	
101008RGBWP	-	-
Model No.	Optics	Finish
101008RGBWP	12 - 12°	TG - Textured Gray
	25 - 25°	AG - Anthracite Gray
	35 - 35°	MB - Matte Black

Job Name/Date:

Fixture Type Designation:





datasheet

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00132	Non-Dim	120VAC to 24VDC, 88W, Class 2	1-2

For other power supply options consult factory.

PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation: