

datasheet


Cloud 9 is a fully uniform, custom-sized LED luminous panel for wall or ceiling mount. Size is customizable and the frame is made of aluminum with five standard finishes, custom finish on request. 24VDC remote power supply.


TECHNICAL DATA

Wattage / Input	Various Based on Size - Consult Factory			
Power Supply	Remote 24VDC			
Construction	Body: Aluminum, Acrylic Lens: Opal Diffuser			
ССТ	3000K, 3500K, 4000K			
CRI	>80			
Delivered Lumens	4560 lm (3000K, 5' x 5' version)			
Efficacy	60 lm/W (3000K, 5' x 5' version)			
Optics	Direct / Indirect			
Finishes	5 Standard, See Below			
Fixture Dimensions	Customizable - Consult Factory			
Lumen Maintenance	L80 >75,000 hrs (Ta 40°C)			
LED Source	LGP LED (OSRAM)			
IP Rating	IP20			



Sample Fixture Dimensions (5' x 5')





ORDERING INFORMATION

Example: CL9-L-30-10-Q-ST-60-60. Power Supplies ordered separately.

·							
	-	-	- Q	-	-	-	
Model No.	ССТ	Finish	Driver	Style	Length	Wide	
CL9-L	27 - 2700K	02 - Black Suede	Q - Remote 24VDC	ST - Standalone	XX - inches	XX - inches	
	30 - 3000K	04 - Bronze	Driver Required	SE - Seamless			
	40 - 4000K	10 - Matte Silver	(dimming drivers				
	50 - 5000K	11 - White Suede96 - Clear AnodizedSatin Aluminum	available)	Values for width r	n must be between 6 in. and 118 in. must be between 6 in. and 81 in. pe rounded to the nearest quarter inch.		

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

1 of 2





datasheet

SUGGESTED POWER SUPPLIES

24VDC - For 60" x 60" (5' x 5') version

Part Number	Description	Input/Output	# of Fixtures
PPLT00284	Non-Dim	120-277VAC to 24VDC, 100W, Class 2, DAMP	1-1
PPLT00543	0-10V dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-1

For other size panels and power supply options, consult factory.

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

2 of 2