

Dot is a indoor surface mounted downlight made of AirCoral® suitable for installation on ceilings. It is available with 1, 3 or 5 light sources with an anti-reflection effect parabola. It has a standard 3000K color temperature and 15° optic.

TECHNICAL DATA

Wattage / Input	1 x 1.5W (500mA) 3 x 1.5W (500mA) 5 x 1.5W (500mA)
Power Supply	Remote, not included. See page 2.
Construction	Body: AirCoral®
CCT	3000K 2700K, 4000K on request
CRI	>90
Delivered Lumens	104 lm per beam (3000K)
Efficacy	69.3 lm/W per beam (3000K)
Optics	15° (30° on request)
Finishes	AirCoral® - suitable for painting
LED Source	COB Professional LED
Fixture Dimensions	See Dimension Drawings
IP Rating	IP20

The body is made of Aircoral® a unique patented composite material that actually purifies the air. It can be calculated how many cubic feet each fixture will purify. See website for Aircoral® calculator.

Additionally, Aircoral® is:

- Antibacterial.
- Antifungal.
- Scratch-resistant.
- Dust-resistant.
- Suitable for painting.
- LEED recognized material.


ORDERING INFORMATION

Example: BU1911.27.AC.US. Power Supplies ordered separately.


		AC	US
Model No.	CCT	Finish	
BU1911 - Dot 1	30 - 3000K	AC - AirCoral®	US
BU1913 - Dot 3	27 - 2700K (on request)		
BU1915 - Dot 5	40 - 4000K (on request)		




Dot 5 - Fixture Dimensions



Dot 3 - Fixture Dimensions



Dot 1 - Fixture Dimensions



Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

500mA

Part Number	Description	Input/Output	# of Fixtures		
			1 x 1.5W	3 x 1.5W	5 x 1.5W
PPLT00497	Phase Dim (120V only)	120VAC to 500mA, 12W, Class 2	2-7	1-2	1-1
PPLT00465-P	0-10V Dimming to 1.0%	120-277VAC to 500mA, 20W, Class 2	1-13	1-4	1-2
PPLT00561-P	0-10V Dimming to 0.1%	120-277VAC to 500mA, 100W, Class 2	2-17	1-5	1-3


Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00259	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 500mA, 10W, Class 2	4-5
PPLT00195	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 500mA, 19W, Class 2	6-11
PPLT00180	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 500mA, 27W, Class 2	12-16

*For other power supply options consult factory.***PHOTOMETRIC DATA***Note all Photometry is 3000K*

Maximum Candela = 480.1

— C0 - C180
— C90 - C270

*Job Name/Date:**Fixture Type Designation:*