

EL LED bollard is an energy efficient luminaire for use in area, street or walkway lighting. Made of extruded aluminum with a silver polyester powder coat or Cor-ten steel finish, it is offered in 3 standard sizes and 5 color temperatures.



EL1250



EL710



EL380

## TECHNICAL DATA

<b>Wattage / Input</b>	See chart - page 2
<b>Power Supply</b>	Integral
<b>Construction</b>	Body/Pole: Extruded Aluminum (optional Cor-ten steel) Lens: PMMA with aluminum support plate Cover: Single-pane safety glass (ESG)
<b>CCT</b>	2200K, 2700K, 3000K, 4000K, 5700K
<b>CRI</b>	>80 (3000K) >70 (2200K, 2700K, 4000K, 5700K)
<b>Delivered Lumens</b>	Lumens depend on light distribution
<b>Optics</b>	EL380 version: AP07 satiné, AS06 satiné only EL710 and EL1250: AH02, AP07, AS06, AS07 (all available in satiné), AS08, AG01, AG02, AG03, AG04-H, AG04-V
<b>Finishes</b>	Silver-Gray (RAL 9007 / DB 702) (Optional Cor-ten Steel)
<b>Fixture Dimensions</b>	See chart - page 2
<b>LED Source</b>	Accommodates up to 3 LED lighting units (LED board: 12 LEDs per element)
<b>IP Rating</b>	IP66
<b>Impact Rating</b>	IK09

Fixture Dimensions - see chart on page 2

See matching pole or wall versions of EL system in the Pole Mounted & Wall Mounted sections of website.

## ORDERING INFORMATION

Example: EL710.

Model No.	LED board	CCT	Light Distribution - Optics		Finishes
EL380	Facade / Object	1 - 2200K	AH02	AS07 satiné	S - Silver-gray
EL710	Walkway / Accent	2 - 2700K	AH02 satiné	AS08	CS - Cor-ten steel
EL1250	(only AP07 Satine and AS06 Satine available on Walkway / Object only)	3 - 3000K	AP07	AG01	
		4 - 4000K	AP07 satiné	AG02	
		5 - 5700K	AS06	AG03	
			AS06 satiné	AG04-H	
			AS07	AG04-V	

For more information on Light Distributions - see page 2



Job Name/Date:

Fixture Type Designation:

## FIXTURE DIMENSIONS CHART

## LIGHTING UNIT OPTIONS

MODEL NO.	WEIGHT (lbs)	H1 (in)	L2 (in)	B1 (in)	LIGHTING ELEMENTS	LED	POWER (W)
EL380	29.8 lbs	17.6"	9.1"	3.3"	1 (1-3 units)	12-36	10-60
EL710	37.5 lbs	28.4"	9.1"	3.3"	1 (1-3 units)	12-36	10-60
EL1250	59.5 lbs	48.9"	9.1"	3.3"	1 (1-3 units)	12-36	10-60



## MODEL / EQUIPMENT VARIATIONS




Pedestrian Path /  
Accent lighting element  
1 Lighting unit



Façade /  
Object lighting element  
1-3 Lighting units

## DIMENSIONS




Job Name/Date:

Fixture Type Designation:

## PHOTOMETRIC DATA

Light Distributions ( also available in satiné version – spot optics excluded )



All light distributions come in Satiné  
See Product Matrix, page 1

Job Name/Date:

Fixture Type Designation: