



# Visible explorer

eye

design by Landa R&D

designplan<sup>TM</sup> 

79 Trenton Avenue  
Frenchtown, NJ 08825

[www.designplan.com](http://www.designplan.com)

Tel: (908) 996-7710  
Fax: (908) 996-7042



# eye 80

*Eye 80 has 5W power and is ideal for recessed ceiling applications, for an accurate light in any outdoor context. Eye's extra-clear transparent tempered glass widens its field of view in three different light emission models: spot, flood and wide floodlight. The body is made in die-cast aluminum. A touch of minimal light for every lighting requirement.*

EYE 80 | CEILING RECESSED





# eye 80

SPOT • FLOOD • WIDE FLOOD

# | 5W

## TECHNICAL SPECIFICATIONS

Source lamp

Total wattage

Voltage

Control

Light color

Delivered lumens  
\*Source lumens

Luminous efficacy

McADAM steps

Beam

CRI

Lifetime

IP rating

IK rating

### SPOT

LED 5W

5W

24VDC

Power supply not included •  
dimmable through power supply

3000K • other colors on request

220 lm (500 lm\*)

44 lm/W

3

20°

> 90

L70 > 50.000 h Ta 40°C

IP65

IK08

### FLOOD

LED 5W

5W

24VDC

Power supply not included • dimmable  
through power supply

3000K • other colors on request

400 lm (500 lm\*)

80 lm/W

3





40°

> 90

L70 > 50.000 h Ta 40°C

IP67

IK08





## TECHNICAL SPECIFICATIONS


Source lamp	LED 5W
Total wattage	5W
Voltage	24VDC
Control	Power supply not included • dimmable through power supply
Light color	3000K • other colors on request
Delivered Lumens *Source lumens	460 lm (500 lm*)
Luminous efficacy	92 lm/W
McADAM steps	3
Beam	60°
CRI	> 90
Lifetime	L70 > 50.000 h Ta 40°C
IP rating	IP67
IK rating	IK08

**WIDE FLOOD**

---







## MATERIALS




<i>Body</i>	Die-cast aluminum EN47100	
<i>Diffuser</i>	Extra clear glass	
<i>Finishing</i>	White polyester powder paint	○

## ORDER CODE

EY 5 0 ISO \_ H B 7 Z U

Beam	<b>S</b> Spot
	<b>F</b> Flood
	<b>W</b> Wide flood

Example EY 5 0 ISO S H B 7 Z U



## INCLUDED ACCESSORIES

<i>Code</i>	<i>Description</i>
-	Housing box

## AVAILABLE ACCESSORIES

<i>Code</i>	<i>Description</i>
00KEY50	Levelling kit
010829600000	Plastering rim
0303003	Suction cup to screw the glass





# eye 125

*Recessed ceiling luminaire ideal for outdoor contexts of any type, with accuracy and infallibility. Eye 125 is a product with a power of 12W, color temperature 3000K (2700K - 4000K on request) and light emission available in three options: spot, flood and wide flood. The die-cast aluminum body guarantees performance and longevity.*

EYE 125 | CEILING RECESSED





# eye 125





# | 12W

SPOT • FLOOD • WIDE FLOOD



## TECHNICAL SPECIFICATIONS



	SPOT	FLOOD
Source lamp	LED 12W	LED 12W
Total wattage	14.5W	14.5W
Voltage	350mA, 50-60Hz	350mA, 50-60Hz
Control	See remote drivers, not included	See remote drivers, not included
Light color	3000K • other colors on request	3000K • other colors on request
Delivered Lumens *Source lumens	785 lm (1500 lm*)	950 lm (1500 lm*)
Luminous efficacy	52 lm/W	63 lm/W
McADAM steps	3	3
Beam	20°	40°
CRI	> 90	> 90
Lifetime	L70 > 50.000 h Ta 40°C	L70 > 50.000 h Ta 40°C
IP rating	IP65	IP65
IK rating	IK08	IK08





## TECHNICAL SPECIFICATIONS

Source lamp	LED 12W
Total wattage	14.5W
Voltage	350mA, 50-60Hz
Control	See remote drivers, not included
Light color	3000K • other colors on request
Delivered lumens *Source lumens	1200 lm (1500 lm*)
Luminous efficacy	80 lm/W
McADAM steps	3
Beam	60°
CRI	> 90
Lifetime	L70 > 50.000 h Ta 40°C
IP rating	IP65
IK rating	IK08

### WIDE FLOOD







## MATERIALS




Body	Die-cast aluminum EN47100
Diffuser	Extra clear glass
Finishing	White polyester powder paint

## ORDER CODE

EY 6 0 ISO \_ HBAZ U

Beam	<b>S</b> Spot
	<b>F</b> Flood
	<b>W</b> Wide flood

Example **EY 6 0 ISO S HBAZ U**



## INCLUDED ACCESSORIES

Code	Description
-	Housing box

## AVAILABLE ACCESSORIES

Code	Description
00KEY60	Levelling kit
010829700000	Plastering rim
0303004	Suction cup to screw the glass









# eye 200

*Eye 200 recessed ceiling is synonymous with high light efficiency and perfect light control. Eye 200 is the best choice for an outdoor environment without shadows. A powerful 20W heart and three types of light emission (spot, flood, wide flood) and standard color temperature 3000K (on request 2700K or 4000K).*

EYE 200 | CEILING RECESSED





# eye 200





# | 20W

SPOT • FLOOD • WIDE FLOOD



## TECHNICAL SPECIFICATIONS


	SPOT	FLOOD
Source lamp	LED 20W	LED 20W
Total wattage	24W	24W
Voltage	500mA, 50-60Hz	500mA, 50-60Hz
Control	See remote drivers, not included	See remote drivers, not included
Light color	3000K • other colors on request	3000K • other colors on request
Delivered lumens *Source lumens	916 lm (2250 lm*)	1400 lm (2250 lm*)
Luminous efficacy	39 lm/W	58 lm/W
McADAM steps	3	3
Beam	20°	40°
CRI	> 90	> 90
Lifetime	L70 > 50.000 h Ta 40°C	L70 > 50.000 h Ta 40°C
IP rating	IP65	IP65
IK rating	IK08	IK08





## TECHNICAL SPECIFICATIONS

<i>Source lamp</i>	LED 20W
<i>Total wattage</i>	24W
<i>Voltage</i>	500mA, 50-60Hz
<i>Control</i>	See remote drivers, not included
<i>Light color</i>	3000K • other colors on request
<i>Delivered lumens</i> <i>*Source lumens</i>	1650 lm (2250 lm*)
<i>Luminous efficacy</i>	69 lm/W
<i>McADAM steps</i>	3
<i>Beam</i>	60°
<i>CRI</i>	> 90
<i>Lifetime</i>	L70 > 50.000 h Ta 40°C
<i>IP rating</i>	IP65
<i>IK rating</i>	IK08

### WIDE FLOOD







## MATERIALS




Body	Die-cast aluminum EN47100
Diffuser	Extra clear glass
Finishing	White polyester powder paint

## ORDER CODE

EY 8 0 ISO\_HBDZ U

Beam	<b>S</b> Spot
	<b>F</b> Flood
	<b>W</b> Wide flood

Example **EY 8 0 ISO S HBDZ U**



## INCLUDED ACCESSORIES

Code	Description
-	Housing box

## AVAILABLE ACCESSORIES

Code	Description
00KEY80	Levelling kit
010829800000	Plastering rim
0303004	Suction cup to screw the glass





