



Elios





Ø 10.24" Ø 7.87" 1.18" 1.18" 8.66"

OTHER AVAILABLE CODES

BU6381.27.AC	lens light color	40° 2700K
BU6381.40.AC	lens light color	40° 4000K (on reques
BU6383.27.AC	lens light color	120° 2700K
BU 6383.40.AC	lens light color	120° 4000K (on reques

TECHNICAL FEATURES

Code	BU6381.AC	BU6383.AC
Type	Downlight 90°	Downlight 90°
Material	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	56.83 ft ²	56.83 ft ²
Weight	5.73 lbs	5.73 lbs
Mounting	Ceiling recessed	Ceiling recessed
IP rating	IP40	IP40
Control gear	Remote Driver	Remote Driver
Cut out for plasterboard	Ø 10.63 in	Ø 10.63 in
Lamp type	LED 1050mA	LED 500mA
	40	#3
Lamp wattage	1 × 40W	2 × 6.5W
Luminous efficacy	1 × 4680 lm - 3000K	2 × 930 lm - 3000K
Light distribution	Wide beam 40°	Wide beam 120°
Fitting	-	-
Light color	White 3000K	White 3000K
Light hole	Ø 7.87 in	Ø 7.87 in
Voltage connection	50/60Hz	50/60Hz
CRI	>90	>90
Note	Extra white satin glass. Frosted glass recessed 1.18 in into the ceiling.	Extra white satin glass. Frosted glass recessed 1.18 in into the ceiling.
	Other available light colors: 2700K, 4000K (on request).	Trailing-edge and leading-edge dimming (20 - 100%).
		Other available light colors: 2700K, 4000K (on request).

OPTIONAL

Brick box - cod. BR6383LT



79 Trenton Avenue Frenchtown, NJ 08825

w.designplan.com

c: (908) 996-7042

^{*} The absorption capacity per ft^3 calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of $8.86\ ft$ in height and therefore expressed in ft^2