

ELOISE

Eloise is a clean and comfortably designed wall installation luminaire radial emission 360°, available with a white or black internal reflector. EN47100 die-cast aluminum made.

Powder polyester coated on treated layer to prevent corrosion, available in five standard colors.

The chemical treatment of aluminum fixtures consists of Cataphoresis process followed by a 60/80micron layer of power polyester coating

- Integral power supply 120VAC 50/60Hz operating
- Power (10W LED; 13W Total) LED MidPower
- CCT: 2700K/3000K/4000K CRI≥80
- Diffuser made in Polycarbonate UV resistant and equipped of water tightened silicon gaskets to ensure IP protection.
- IP65
- IK07
- Inox fixing clamp and IP gel connector included.

designplan® 

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042










WALL





White Reflector

ELOISE 360° 10W LED 13W Total 120VAC



						
		<i>white</i>	<i>sand</i>	<i>graphite</i>	<i>aluminum</i>	<i>corten</i>
2700K	855 lm	901431002	901431003	901431004	901431005	901431008
3000K	900 lm	901411002	901411003	901411004	901411005	901411008
4000K	945 lm	901421002	901421003	901421004	901421005	901421008










Black Reflector

ELOISE 360° 10W LED 13W Total 120VAC



						
		<i>white</i>	<i>sand</i>	<i>graphite</i>	<i>aluminum</i>	<i>corten</i>
2700K	413 lm	901431012	901431013	901431014	901431015	901431018
3000K	437 lm	901411012	901411013	901411014	901411015	901411018
4000K	459 lm	901421012	901421013	901421014	901421015	901421018

