

FA100-C

The FA100-C is an outdoor, ceiling mounted LED luminaire with downward light emission, that is energy efficient and offers different light distributions for use in covered walkways, underpasses and archways.



FA100-C (8 LED)



FA100-C (16 LED)

Fixture Dimension
See chart on page 2

TECHNICAL DATA

Wattage / Input	4.8W - 12.3W
Power Supply	Integral (120-277VAC)
Construction	Body: EN44300 Die-Cast Aluminium Cover: Single-Pane Safety Glass (ESG) 0.24" thick
CCT	2200K, 2700K, 3000K, 4000K
CRI	3000K >80 2200K, 2700K, 4000K, >70
Delivered Lumens	612-1325 lm (8 LED, 3000K)
Efficacy	126.5-108.1 lm/W (8 LED, 3000K)
Optics	AH02, AS08 (see below)
Finishes	Silver-Gray (RAL 9007 / DB 702) Other Colors on Request
Fixture Dimensions	4.13" w x 7.87" l x 4.02" h
Fixture Weight	9.92 lbs
IP Rating	IP66
Impact Rating	IK09 (IK10 on request)
Lateral Windage Area	0.215 ft ²

ORDERING INFORMATION


Example: FA100-C-16-30-AH02-S.

FA-100C	-		-		-	
Model No.	LED	CCT	Optics	Finishes		
FA100-C	08 - 8 LED 16 - 16 LED	22 - 2200K 27 - 2700K 30 - 3000K 40 - 4000K	AH02 - AH02 Symmetric Wide Flood AS08 - AS08 Asymmetric Side or Forward Throw	S - Silver-gray C - Custom (consult factory)		


Job Name/Date:

Fixture Type Designation:


FIXTURE DIMENSIONS




MODEL #	L1 (in)	H1 (in)	B1 (in)
FA100-WD	4.9"	3.2"	7.9"
FA100-WU	4.9"	3.2"	7.9"
FA100-C	4.0"	4.1"	7.9"



LIGHT DISTRIBUTIONS



AH02
Symmetric Wide Flood



AS08
Asymmetric Side and Forward Throw

Job Name/Date:

Fixture Type Designation: