


FIREFLY PENDANT

FIREFLY is an outdoor luminaire with a poetic soul that comes as a bollard or a pendant light. FIREFLY pendant is perfect for gardens, gazebos, pergolas and to create lighting effects on plants and trees. It has a unique installation system that makes it adaptable to most outdoor needs. Available in static white (RGBW on request) and 4 standard finishes.



Fixture Dimensions



TECHNICAL DATA

Wattage	2W (24VDC)
Power Supply	Remote, not included. See page 2.
Construction	Body: Extruded aluminum EN AW6026 Lens: Opal PMMA (Acrylic) Cable Length: 1.64' (included)
CCT	2700K, 3000K
BUG Rating	B0-U2-G0
CRI	>90
Delivered Lumens	119 lm (3000K)
Efficacy	59.5 lm/W
Optics	360° Diffuse
Finishes	4 Standard, See Below
Fixture Dimensions	Ø2.0" x 7.5"
Fixture Weight	0.99 lbs
Lumen Maintenance	L80, B15 >60,000hrs (Ta 40°C)
Color Consistency	3-Step MacAdam
IP Rating	IP65
Impact Resistance	IK08

ORDERING INFORMATION

Example: LNF130SOSXHB7ZD.US. Power Supplies / Accessories ordered separately.

LNF1	30	SOSX		B7Z		US
Model No.	Mounting		CCT	Power	Finish	
LNF1	30 - Cable	SOSX - Suspension	Y - 2700K H - 3000K	B7Z - Remote	L - Graphite V - Oxide H - Gray D - Green	US

Job Name/Date:

Fixture Type Designation:

ACCESSORIES - Installation



CABLE CLAMP STRIP
Included

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00586	Non-Dim	120-277VAC to 24VDC, 40W, Class 2	1-16
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	5-40

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00273	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 40W, Class 2	1-16
PPLT00530	L3D0	L3D0	100%-0.1%	Hi-Lume™ Premier 0.1% or Ecosystem 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-38

DRIVERS IN NEMA ENCLOSURE

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715

Part Number	Description	Input/Output	# of Fixtures 2W
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-38

For other power supply options consult factory.


Job Name/Date:

Fixture Type Designation:

PHOTOMETRIC DATA

Note all Photometry is 3000K

Maximum Candela = 11.7



PHOTOMETRIC FILENAME : FI30S0SXHB7ZX 24VDC SUSPENDED.IES

Job Name/Date:

Fixture Type Designation: