

# FIREFLY PENDANT


FIREFLY is an outdoor luminaire with a poetic soul that comes as a bollard or a pendant light. FIREFLY pendant is perfect for gardens, gazebos, pergolas and to create lighting effects on plants and trees. It has a unique installation system that makes it adaptable to most outdoor needs. Available in static white (RGBW on request) and 4 standard finishes.



## TECHNICAL DATA

<b>Wattage</b>	2W (24VDC)
<b>Power Supply</b>	Remote, not included. See page 2.
<b>Construction</b>	Body: Extruded aluminum EN AW6026 Lens: Opal PMMA (Acrylic) Cable Length: 1.64' (included)
<b>CCT</b>	2700K, 3000K
<b>BUG Rating</b>	B0-U2-G0
<b>CRI</b>	>90
<b>Delivered Lumens</b>	119 lm (3000K)
<b>Efficacy</b>	59.5 lm/W
<b>Optics</b>	360° Diffuse
<b>Finishes</b>	4 Standard, See Below
<b>Fixture Dimensions</b>	Ø2.0" x 7.5"
<b>Fixture Weight</b>	0.99 lbs
<b>Lumen Maintenance</b>	L80, B15 >60,000hrs (Ta 40°C)
<b>Color Consistency</b>	3-Step MacAdam
<b>IP Rating</b>	IP65
<b>Impact Resistance</b>	IK08

Fixture Dimensions



## ORDERING INFORMATION

Example: LNF130SOSXHB7ZD.US. Power Supplies / Accessories ordered separately.

LNF1	30	SOSX		B7Z		US
<b>Model No.</b>	<b>Mounting</b>		<b>CCT</b>	<b>Power</b>	<b>Finish</b>	
LNF1	30 - Cable	SOSX - Suspension	Y - 2700K H - 3000K	B7Z - Remote	L - Graphite V - Oxide H - Gray D - Green	US

Job Name/Date:

Fixture Type Designation:

## ACCESSORIES - Installation



**CABLE CLAMP STRIP**  
Included

## SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00149</a>	Non-Dim	120VAC to 24VDC, 10W, Class 2, IP65	1-4
<a href="#">PPLT00632</a>	0-10V Dimming (Dim to Off)	120-277VAC to 24VDC, 12W, Class 2	1-4
<a href="#">PPLT00155</a>	Non-Dim	120VAC to 24VDC, 30W, Class 2	1-12
<a href="#">PPLT00586</a>	Non-Dim	120-277VAC to 24VDC, 40W, Class 2	1-16
<a href="#">PPLT00709</a>	ELV / TRIAC & 0-10V Dimming	120-277VAC to 24VDC, 96W, Class 2, DAMP	1-38
<a href="#">PPLT00543</a>	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	5-40


## Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
<a href="#">PPLT00273</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 40W, Class 2	1-16
<a href="#">PPLT00530</a>	L3D0	L3D0	100%-0.1%	Hi-Lume™ Premier 0.1% or Ecosystem 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-38

For other power supply options consult factory.

## PHOTOMETRIC DATA

Note all Photometry is 3000K



Job Name/Date:

Fixture Type Designation: