

## Technical features

IP65 IK09 NEW




402803P

## FRAME MAXI ROUND

Designed by  
NAVA + AROSIO

Round Ø11.2" surface mounted luminaire for outdoor installation on a façade/wall. Phospho-chromatized and polyester powder coated die-cast copper-free aluminum body, acid-etched tempered glass diffuser white painted internally, molded silicone gasket and stainless steel screws. Remote LED driver 700mA 50-60Hz, with 48 x mid-power SAMSUNG 2835 LED. IP65 rating.



402803EMP

OPTIONAL VERSION  
WITH 3H EMERGENCY

Available on request

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
high-power led	diffused	1,010	50.50
<b>4000°K neutral-white</b>			
high-power led	diffused	1,055	52.75

### Finish color options:

 Textured Grey  
RAL 9006

 Anthracite Grey  
RAL 7016

 Matte Black  
(on request)

### Technical data

Wattage	20 WATT
IP Rating	IP65
IK Rating	IK09
Material	High corrosion resistance extruded copper-free aluminum body
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	48 x mid-power SAMSUNG 2835 LED
Screws	Stainless steel
Transformer	Remote electronic power supply 700mA 50/60Hz
Gasket	Silicone rubber
Glass	Acid-etched tempered glass diffuser - white painted internally
Power cable	0.98' power cable included
Gross weight	9.26 lbs

