FLASH MAXI COB




datasheet

Flash are a family of round floodlights for outdoor installation on a façade or wall. It is available in a medium, maxi or mega version with various optics and 3 standard finishes.

c Untertal



Fixture Dimensions:



TECHNICAL DATA

Wattage / Input	36W (120VAC)		
Power Supply	Integral		
Construction	Body: Die-Cast Copper-Free Aluminum		
	Lens: Tempered Safety Glass		
	Cable Length: 3.28'		
ССТ	3000K, 4000K		
BUG Rating	B0-U5-G0		
Delivered Lumens	2277 lm (3000K)		
Efficacy	63.3 lm/W (3000K)		
Optics	35°		
Finishes	Textured Gray, Anthracite Gray,		
	Matte Black (on request)		
Fixture Dimensions	Ø7.79" x 10.91"		
Fixture Weight	7.7 lbs		
LED Source	1 CREE CXB 2530 COB LED		
IP Rating	IP65		
IK Rating	IK09		

ORDERING INFORMATION

Example: 101104P-30K-35-MB

101104P	-	- 35	-
Model No.	ССТ	Optic	Finish
101104P	30K - 3000K 40K - 4000K	35 - 35°	TG - Textured Gray AG - Anthracite Gray MB - Matte Black (on request)

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

1 of 2

FLASH MAXI COB



datasheet

ACCESSORIES Anti-Glare



AC-027P-xx

Anti-Glare Visor - For Flash Maxi version Include one of the below finishes:


TG - Textured Gray

AG - Anthracite Gray

MB - Matte Black (on request)

PHOTOMETRIC DATA





Job Name/Date:

Fixture Type Designation: