### **FLASH MAXI**



datasheet

Flash are a family of round floodlights for outdoor installation on a façade or wall. It is available in a medium, maxi or mega version with various optics and 3 standard finishes.


# c Lintertek



#### **TECHNICAL DATA**

Wattage / Input	12W (120VAC)		
Power Supply	Integral		
Construction	Body: Die-Cast Copper-Free Aluminum		
	Lens: Tempered Safety Glass		
	Cable Length: 3.28'		
ССТ	3000K, 4000K		
BUG Rating	B0-U5-G0		
Delivered Lumens	1201 lm (3000K, 10°)		
Efficacy	100 lm/W (3000K, 10°)		
Optics	3 Standard, See Below		
Finishes	Textured Gray, Anthracite Gray,		
	Matte Black (on request)		
Fixture Dimensions	Ø7.79" x 10.91"		
Fixture Weight	7.7 lbs		
LED Source	8 CREE "XP-G3" High Power LEDs		
IP Rating	IP65		
IK Rating	IK09		

#### Fixture Dimensions:



#### **ORDERING INFORMATION**

Example: 101103P-30K-10-MB

101103P	-	-	-
Model No.	ССТ	Optics	Finish
101103P	<b>30K</b> - 3000K <b>40K</b> - 4000K	<b>10</b> - 10° <b>30</b> - 30° <b>45</b> - 45°	TG - Textured Gray AG - Anthracite Gray MB - Matte Black (on request)

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

1 of 2

datasheet

## ACCESSORIES Anti-Glare



#### AC-027P-xx

Anti-Glare Visor - For Flash Maxi version Include one of the below finishes:


TG - Textured Gray


AG - Anthracite Gray


MB - Matte Black (on request)

#### PHOTOMETRIC DATA

Note: All photometry is 3000K







Job Name/Date:

Fixture Type Designation: