


Focus is a square recessed downlight with a rounded light emission hole. It is made of AirCoral® paintable plaster, and is suitable for indoor installation on ceilings. It is available in 3000K as standard with a 40° light beam.



## TECHNICAL DATA

<b>Wattage / Input</b>	10W (500mA)
<b>Power Supply</b>	Remote, not included. See page 2.
<b>Construction</b>	Body: AirCoral® Lens: Frosted Glass
<b>CCT</b>	3000K (2700K, 4000K on request)
<b>CRI</b>	>90
<b>Delivered Lumens</b>	557 lm (3000K)
<b>Efficacy</b>	61.9 lm/W
<b>Optics</b>	40°
<b>Finishes</b>	AirCoral® Plaster
<b>Fixture Dimensions</b>	5.71" l x 5.71" w x 5.51" h
<b>Cutout Dimensions</b>	6.10" x 6.10"
<b>Aperature</b>	3.54" x 3.54"
<b>Fixture Weight</b>	3.97 lbs
<b>IP Rating</b>	IP40

Fixture Dimensions



The body is made of AirCoral® a unique patented composite material that actually purifies the air. It can be calculated how many cubic feet each fixture will purify. See website for AirCoral® calculator.

Additionally, AirCoral® is:

- Antibacterial.
- Antifungal.
- Scratch-resistant.
- Dust-resistant.
- Suitable for painting.
- LEED recognized material.

## ORDERING INFORMATION

Example: BU6163.Z.AC.30.US. Power supplies ordered separately.

BU6163.Z	AC		.US
Model No.	Material	CCT	
BU6163.Z	AC - AirCoral®	30 - 3000K (standard) 27 - 2700K (on request) 40 - 4000K (on request)	

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

500mA

Part Number	Description	Input/Output	Fixtures
<a href="#">PPLT00154</a>	0-10V Dimming to 10%	120-277VAC to 500mA, 12W, Class 2	1-1
<a href="#">PPLT00469</a>	Phase Dim (120V only)	120VAC to 500mA, 14W, Class 2	1-1
<a href="#">PPLT00465-P</a>	0-10V Dimming to 1.0%	120-277VAC to 500mA, 20W, Class 2, DAMP	1-2
<a href="#">PPLT00308-P</a>	0-10V Dimming to 0.1%	120-277VAC to 500mA, 30W, Class 2, DAMP	1-2
<a href="#">PPLT00467-P</a>	0-10V Dimming to 1.0%	120-277VAC to 500mA, 50W, Class 2, DAMP	1-2

## Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
<a href="#">PPLT00195</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 500mA , 19W, Class 2	1-1
<a href="#">PPLT00180</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 500mA , 27W, Class 2	2-2


For other power supply options consult factory.

## ACCESSORIES

Installation - Consult Factory for Back Box

## PHOTOMETRIC DATA

Note: All photometry is 3000K.



PHOTOMETRIC FILENAME : FOCUS BU6163.Z.AC 3000K 9W.IES

Job Name/Date:

Fixture Type Designation: