




datasheet





ADA Compliant

Fixture Dimensions



17.72"

TECHNICAL DATA

3000K standard with 120° optics.

Wattage / Input	6.5W (350mA)		
Power Supply	Remote, not included. See page 2.		
Construction	Body: AirCoral®		
ССТ	3000K		
CRI	>90		
Delivered Lumens	810 lm (3000K)		
Efficacy	124.6 lm/W		
Optics	120°		
Finishes	AirCoral®		
	14: Gold Leaf on request		
Fixture Dimensions	17.72" l x 17.72" w x 3.94" h		
IP Rating	IP20		
IK Rating	-		

Frame is an indoor surface mounted wall lamp made of AirCoral® that available in a variety of finishes including "golden leaf". It is available in

The body is made of Aircoral® a unique patented composite material that actually purifies the air. It can be calculated how many cubic feet each fixture will purify. See website for Aircoral® calculator.

Additionally, Aircoral® is:

Antibacterial.

Antifungal.

Scratch-resistant.

Dust-resistant.

Suitable for painting.

LEED recognized material.

ORDERING INFORMATION

Example: BU2808.AC.US. Power Supplies ordered separately.

	. us
Model No.	
BU2808.AC BU2808.AC.14 (gold leaf)	US

Job Name/Date: Fixture Type Designation:

F: 908-996-7042

P: 908-996-7710





datasheet

SUGGESTED POWER SUPPLIES

350mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00466-P	0-10V Dimming to 1.0%	120-277VAC to 350mA, 6W, Class 2	1-1
PPLT00465-P	0-10V Dimming to 1.0%	120-277VAC to 350mA, 20W, Class 2	1-1

For other power supply options consult factory.

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

2 of 2