


Gem is a series of compact, surface mounted floodlights for indoor installation in residential and commercial environments, particularly shop windows and display cabinets in retail and museums. It is available in 3 different sizes - Gem 2.1 is 1.57" long with a diameter of 1.26" and adjustable 230° - 3 color temperatures and 3 standard finishes.

TECHNICAL DATA

Wattage / Input	4.5W (350mA)
Power Supply	Remote, not included. See page 2.
Construction	Body: Anticorodal Aluminum Bracket: Aluminum Cable Length: 4.92' (other lengths available - see page 2)
CCT	2700K, 3000K, 4000K
CRI	>90
Delivered Lumens	280 lm (3000K, 23°)
Efficacy	62.2 lm/W (3000K, 23°)
Optics	4 Standard (see below)
Finishes	3 Standard, Custom RAL on request (see below)
Fixture Dimensions	Ø1.26" x 1.57" h
Base Size	0.79" x 0.79"
Fixture Weight	0.16 lbs
LED Source	1 Power LED
Lumen Maintenance	L90, B10 >50,000hrs (Ta 25°C)
Color Consistency	3-Step MacAdam
Operating Temp.	32°F to +113°F
IP Rating	IP40



Fixture Dimensions



ORDERING INFORMATION

Example: GE2120100150MB. Power Supplies / Accessories ordered separately.

GE21201				
Model No.	Optical Accessories	CCT	Optics	Finish
GE21201	000 - none 001 - Honeycomb Louvre	F0 - 2700K 50 - 3000K 90 - 4000K	S - 16° M - 23° F - 33° L - 42°	N - Black P - Pearl Chrome B - White C - Custom RAL (Consult factory for "C")

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

350mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00148	0-10V Dimming to 10%	120-277VAC to 350mA, 6W, Class 2	1-1
PPLT00496	Phase Dim (120V only)	120VAC to 350mA, 12W, Class 2, DAMP	1-2
PPLT00480-P	0-10V Dimming to 1.0%	120-277VAC to 350mA, 30W, Class 2, DAMP	1-4
PPLT00263	Leading / Trailing Edge Dimming to 10% (120V only)	120-277VAC to 350mA, 32W, Class 2	2-3
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 50W, Class 2	1-4
PPLT00561-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 100W, Class 2	1-4

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00247	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 7W, Class 2	1-1
PPLT00516	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 13W, Class 2	2-2
PPLT00179	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 19W, Class 2	3-4

*For other power supply options consult factory.***ACCESSORIES - Installation****Cables to be ordered with fixture***Your choice of length***WF0600** - Gray - 4.92' (1.5 m) standard**WF4000** - Black - 4.92' (1.5 m) standard***Other lengths are available in 5 meter increments.***


Ex: 16.40' (5 m), 32.81' (10 m), 49.21' (15 m), 65.62' (20 m)

*Job Name/Date:**Fixture Type Designation:*

PHOTOMETRIC DATA


Note all Photometry is 3000K

Maximum Candela = 2231.6




PHOTOMETRIC FILENAME : GEM 2.1 S 16° [3000K 4.5W 350MA].IES

Maximum Candela = 1208.6




PHOTOMETRIC FILENAME : GEM 2.1 M 23° [3000K 4.5W 350MA].IES

Maximum Candela = 623.9



PHOTOMETRIC FILENAME : GEM 2.1 F 33° [3000K 4.5W 350MA].IES

Maximum Candela = 400.9



PHOTOMETRIC FILENAME : GEM 2.1 L 42° [3000K 4.5W 350MA].IES

Job Name/Date:

Fixture Type Designation: