

GEM MINI 1


Gem is a series of compact, surface mounted floodlights for indoor installation in residential and commercial environments, particularly shop windows and display cabinets in retail and museums. It is available in 3 different sizes - Gem Mini 1 being the smallest at 0.79" long with a diameter of 0.47" and adjustable 250° - 3 color temperatures and 3 standard finishes.



TECHNICAL DATA

Wattage / Input	1W (350mA)
Power Supply	Remote, not included. See page 2.
Construction	Body: Anticorodal Aluminum Bracket: Aluminum Cable Length: 4.92' standard (other lengths available - see page 2)
CCT	2700K, 3000K, 4000K
CRI	>90
Delivered Lumens	51 lm (3000K, 36°)
Efficacy	51 lm/W (3000K, 36°)
Optics	3 Standard (see below)
Finishes	3 Standard, Custom RAL on request (see below)
Fixture Dimensions	Ø0.47" x 0.79" h
Base Size	0.39" x 0.43"
Fixture Weight	0.05 lbs
LED Source	1 Power LED
Lumen Maintenance	L90, B10 >50,000hrs (Ta 25°C)
Color Consistency	3-Step MacAdam
Operating Temp.	32°F to +113°F
IP Rating	IP40

Fixture Dimensions



ORDERING INFORMATION

Example: GE01201000F0FP. Power Supplies / Accessories ordered separately.

GE01201000			
Model No.	CCT	Optics	Finish
GE01201000	F0 - 2700K 50 - 3000K 90 - 4000K	M - 23° F - 36° L - 48°	N - Black P - Pearl Chrome B - White C - Custom RAL (Consult factory for "C")

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

350mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00138	0-10V Dimming to 10%	120-277VAC to 350mA, 4W, Class 2	2-3
PPLT00496	Phase Dim (120V only)	120VAC to 350mA, 12W, Class 2, DAMP	3-9
PPLT00480-P	0-10V Dimming to 1.0%	120-277VAC to 350mA, 30W, Class 2, DAMP	1-16
PPLT00263	Leading / Trailing Edge Dimming to 10% (120V only)	120-277VAC to 350mA, 32W, Class 2	9-13
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 50W, Class 2, DAMP	1-16
PPLT00561-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 100W, Class 2	2-16

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00247	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 7W, Class 2	4-5
PPLT00516	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 13W, Class 2	7-11
PPLT00179	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 19W, Class 2	13-16

For other power supply options consult factory.

ACCESSORIES - Installation

Cables to be ordered with fixture

Your choice of length

WF0600 - Gray - 4.92' (1.5 m) standard

WF4000 - Black - 4.92' (1.5 m) standard

Other lengths are available in 5 meter increments.

Ex: 16.40' (5 m), 32.81' (10 m), 49.21' (15 m), 65.62' (20 m)


Job Name/Date:

Fixture Type Designation:

PHOTOMETRIC DATA


Note all Photometry is 3000K

Maximum Candela = 95.8




PHOTOMETRIC FILENAME : GEM MINI 1 F 36° [3000K 1W 350MA].IES

Maximum Candela = 46.2



PHOTOMETRIC FILENAME : GEM MINI 1 L 48° [3000K 1W 350MA].IES

Maximum Candela = 174.9



PHOTOMETRIC FILENAME : GEM MINI 1 M 23° [3000K 1W 350MA].IES

Job Name/Date:

Fixture Type Designation: