



5.51" 5.31"



OPTIONAL

Honeycomb: anti-glare screen



Ø0.79" 4.92"

Genius Black



OTHER AVAILABLE CODES

BU1871.AC 4 24 M _ WD	lens	24°
	light color	
	27	2700K
	30	3000K
	40	4000K (on request)
BU1871.27.AC	lens light color	40° 2700K
BU1871.40.AC	lens light color	40° 4000K (on request)
example of code composition	BU1872.AC 4 R 24 M 30 WD	

TECHNICAL FEATURES

Code BU1871.AC Type Downlight 90° Material AC: AirCoral® 14.96 ft² Absorption capacity* Weight 1.76 lbs Mounting Ceiling recessed IP rating IP20 Remote constant current electronic driver (not included) Control gear Cut out for plasterboard 5.31×4.33 in LED 700mA Lamp type **⇒** Vf: 11.5 VDC 1 × 8.5W Lamp wattage Luminous efficacy 1 × 1000 lm - 3000K Light distribution Wide beam 40° Fitting Light color White 3000K Light hole Ø 0.79 in

Voltage connection By driver (optional) >90 Note

Other available light colors: 2700K,

4000K (on request). Other available beams: 24°.

OPTIONAL

CRI

Brick box cod. BR1871LT cod. ACC0053 Honeycomb screen

cod. BR1872LT cod. ACC0053



79 Trenton Avenue Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710 Fax: (908) 996-7042

 $^{^{\}star}$ The absorption capacity per $\mbox{ft}^{\mbox{\tiny 3}}$ calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of $\bf 8.86~ft$ in height and therefore expressed in $\bf ft^2$