





OPTIONAL Honeycomb: anti-glare screen





Ø0.79" 4.92"

Genius Brass





OTHER AVAILABLE CODES

BU1861.AC 4 24 M _ WD	lens	24°
	light color	
	27 30	2700K 3000K
	40	4000K (on request)
BU1861.27.AC	lens light color	40° 2700K
BU1861.40.AC	lens light color	40° 4000K (on request)
example of code composition	BU1862.AC 4 R 24 M 30 WD	

TECHNICAL FEATURES

	-,
Code	BU1861.AC
Туре	Downlight 90°
Material	AC: AirCoral®
Absorption capacity*	14.96 ft ²
Weight	1.76 lbs
Mounting	Ceiling recessed
IP rating	IP20
Control gear	Remote constant current electronic driver (not included
Cut out for plasterboard	5.31×4.33 in
Lamp type	LED 700mA
	3 √f: 11.5 VDC
Lamp wattage	1 × 8.5W
Luminous efficacy	1 × 1000 lm - 3000K
Light distribution	Wide beam 40°
Fitting	-
Light color	White 3000K
Light hole	Ø 0.79 in
Voltage connection	By driver (optional)
CRI	>90
Note	Other available light colors: 2700K, 4000K (on request).

OPTIONAL

cod. BR1862LT Brick box cod. BR1861LT cod. ACC0053 cod. ACC0053 Honeycomb screen

Other available beams: 24°.



79 Trenton Avenue Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710 Fax: (908) 996-7042

^{*} The absorption capacity per ft^3 calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 8.86~ft in height and therefore expressed in ft^2

