


GENIUS


1000 lm IN JUST 0.79 in DIAMETER,
EASY MAINTENANCE




Villa Bogogno Golf Resort, Novara | Negri Illuminazione | ph. Le Michéte Creative Studio

LED replacement in
seconds
and without tools


PUSH & PULL TECHNOLOGY



No need for an inspection hatch. The electrical part can be extracted straight from the light hole just with a simple manual gesture, thanks to the push-pull mechanism which makes it easy to extract and replace the LED source for maintenance purposes.



* The absorption capacity per ft^2 calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 8.86 ft in height and therefore expressed in ft^2 .



Genius



OTHER AVAILABLE CODES

BU1851.AC 4 24 M	WD	lens	24°
light color			
27		2700K	
30		3000K	
40		4000K (on request)	



BU1851.27.AC	lens	40°
	light color	2700K

BU1851.40.AC	lens	40°
	light color	4000K (on request)


example of code composition
BU1851.AC 4 R 24 M 30 WD



OPTIONAL
Honeycomb: anti-glare screen
for proper light directionality.



OPTIONAL
Honeycomb: anti-glare screen
for proper light directionality.



TECHNICAL FEATURES


Code	BU1851.AC
Type	Downlight 90°
Material	AC: AirCoral®
Absorption capacity*	14.96 ft ²
Weight	1.76 lbs
Mounting	Ceiling recessed
IP rating	IP65
Control gear	Remote constant current electronic driver (not included)
Cut out for plasterboard	5.31 x 4.33 in
Lamp type	LED 500mA
	Vf: 11.5 VDC
Lamp wattage	1 x 6W
Luminous efficacy	1 x 1000 lm - 3000K
Light distribution	Wide beam 40°
Fitting	-
Light color	White 3000K
Light hole	Ø 0.79 in
Voltage connection	By driver (optional)
CRI	>90
Note	Other available light colors: 2700K, 4000K (on request). Other available beams: 24°.

OPTIONAL

Brick box
Honeycomb screen

cod. BR1851LT
cod. ACC0053

cod. BR1855LT
cod. ACC0053




GENIUS IP65
see page 395

designplan®

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042




Alessandro Borghese - Il Lusso della Semplicità, Venice | Arch. A. Canelli | ph. Le Michéte Creative Studio

* The absorption capacity per ft² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 8.86 ft in height and therefore expressed in ft².



Villa Bogogno Golf Resort, Novara | Negri Illuminazione | ph. Le Michéte Creative Studio



Genius Kelvin



OTHER AVAILABLE CODES

BU1874.AC 4 R	M	WD
light color		
22	2200K	
24	2400K	
35	3500K	
lens		
24	24°	
40	40°	

example of code composition

BU1874.AC 4 R 24 M 35 WD



TECHNICAL FEATURES

Code	BU1874.AC
Type	Downlight 90°
Material	AC: AirCoral®
Absorption capacity*	14.96 ft ²
Weight	1.76 lbs
Mounting	Ceiling recessed
IP rating	IP65
Control gear	Remote constant current electronic driver (not included)
Cut out for plasterboard	5.31 x 4.33 in
Lamp type	LED 350mA
	Vf: 18 VDC
Lamp wattage	1 x 6W
Luminous efficacy	1 x 720 lm - 2200K 1 x 790 lm - 2400K 1 x 910 lm - 3500K
Light distribution	Wide beam 24° 40°
Fitting	-
Light color	White 2200K 2400K 3500K
Light hole	Ø 0.79 in
Voltage connection	By driver (optional)
CRI	>90

OPTIONAL

Brick box

cod. BR1855LT



designplan®


79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042

Villa Bogogno Golf Resort, Novara | Negri Illuminazione | ph. Le Michéte Creative Studio

* The absorption capacity per ft² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 8.86 ft in height and therefore expressed in ft².



Twin Genius



OTHER AVAILABLE CODES

BU1852.AC 4 24 M _ WD	lens	24°
light color		
27	2700K	
30	3000K	
40	4000K (on request)	

BU1852.27.AC	lens	40°
	light color	2700K

BU1852.40.AC	lens	40°
	light color	4000K (on request)


example of code composition
BU1852.AC 4 R 40 M 30 WD

TECHNICAL FEATURES


Code	BU1852.AC
Type	Downlight 90°
Material	AC: AirCoral®
Absorption capacity*	29.92 ft ²
Weight	4.41 lbs
Mounting	Ceiling recessed
IP rating	IP20
Control gear	Remote constant current electronic driver (not included)
Cut out for plasterboard	8.07 x 5.31 in
Lamp type	LED 500mA
Lamp wattage	2 x 6W
Luminous efficacy	2 x 1000 lm - 3000K
Light distribution	Wide beam 40°
Fitting	-
Light color	White 3000K
Light hole	Ø 0.79 in
Voltage connection	By driver (optional)
CRI	>90
Note	Other available light colors: 2700K, 4000K (on request). Other available beams: 24°.

OPTIONAL

Brick box	cod. BR1852LT
Honeycomb screen	cod. ACC0053



SUPERFUTUREDESIGN®



designplan®

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042

DOUBLE LUMINOUS EFFICIENCY
AND EASY MAINTENANCE
INDEPENDENT PUSH-PULL MECHANISMS

* The absorption capacity per ft² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 8.86 ft in height and therefore expressed in ft².