

4.92"





# Geniusquare Brass





OTHER AVAILABLE CODES

27

30

40

24

2700K

3000K

BU1896.AC 4 R 24 E 30 WD

4000K (on request)

## 

BU1895.AC 4 R \_ E \_ WD

example of code

### **TECHNICAL FEATURES**

Code BU1895.AC XX Type Downlight 90°  $\Delta$ Material AC: AirCoral® 14.96 ft<sup>2</sup> Absorption capacity\* Weight 1.76 lbs Mounting Ceiling recessed IP rating IP20 Control gear Remote constant current electronic driver (not included) Cut out for plasterboard  $5.31 \times 4.33$  in

LED 700 mA Lamp type **■**D Vf: 11.5 VDC

1 × 8.5W Lamp wattage 1 × 1000 lm - 3000K Luminous efficacy Wide beam 24° I 40° Light distribution

Light color

White 3000K White 2700K | 4000K (on request)  $0.79\times0.79$  in Light hole

By driver (optional) Voltage connection >90

#### **OPTIONAL**

Brick box cod. BR1895LT cod. BR1896LT



79 Trenton Avenue Frenchtown, NJ 08825

www.designplan.com

<sup>\*</sup> The absorption capacity per ft3 calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 8.86 ft in height and therefore expressed in ft<sup>2</sup>