


GENIUS BASIC NAKED IP65



The Genius Basic Naked IP65 is an outdoor version of the Genius Basic Naked with a protection rating of IP65. It is **installed from above** by being glued on wood, cement, mirror or marble, with a thickness of from 0.16" to a maximum of 1.18". Once installed the discreet aperture of 1.0" disappears into the surround.

TECHNICAL DATA

Wattage / Input	4W (500mA)
Power Supply	Remote, not included. See page 2.
Construction	Body: Aluminum, Steel
CCT	3000K (standard) (2700K, 4000K on request, consult factory)
CRI	>90
Delivered Lumens	239 lm (3000K)
Efficacy	59.8 lm/W
Optics	24°
Finishes	Black
Fixture Dimensions	5.51 l x 3.15 w x 3.15" h
Aperture	Ø0.98"
Fixture Weight	1.43 lbs
LED Source	1 COB Professional LED
IP Rating	IP65




Fixture Dimensions:



ORDERING INFORMATION

Example: BU2071BL4R24M.30.WD.US. Power Supplies ordered separately.

BU2071BL4R24M		WD.US
Model No.	CCT	
BU2071BL4R24M	30 - 3000K (standard) 27 - 2700K (on request) 40 - 4000K (on request)	WD.US



Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

500mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00497	Phase Dim (120V Only)	120VAC to 500mA, 12W, Class 2	1-3
PPLT00465-P	0-10V Dimming to 1.0%	120-277VAC to 500mA 20W, Class 2	1-5
PPLT00262	Leading / Trailing Edge Dimming to 10% (120V Only)	120-277VAC to 500mA, 32W, Class 2	4-6
PPLT00309-P	0-10V Dimming to 1.0%	120-277VAC to 500mA, 50W, Class 2, DAMP	1-8

Suggested Lutron Compatible Drivers


Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	Fixtures
PPLT00259	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC, 10W	2-2
PPLT00195	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC, 19W	3-4
PPLT00180	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC, 27W	6-6

For other power supply options consult factory.

PHOTOMETRIC DATA

Note: All photometry is 3000K

Maximum Candela = 892.6



PHOTOMETRIC FILENAME : GENIUS BASIC NAKED - BU1071BL4R24M.IES

REPLACEMENT BULBS

Example: MBGB2-L150-30.UL.US

Model No.

MBGB2-L150-27.UL.US - Replacement Lamps - 2700K

MBGB2-L150-30.UL.US - Replacement Lamps - 3000K

Job Name/Date:

Fixture Type Designation: