

## Technical features

IP65 IK08




402401P

# HORIZON MINI 01

Designed by  
PAOLO VILLA

Applique of rectangular shape for outdoor installation on a facade/wall, with single (1 side) light emission. Phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered frosted safety glass, molded silicone gasket and stainless steel screws.

Integral 120VAC 50-60Hz, with 10 mid-power CREE XH-G LED. IP65 rating.



## Technical data

|              |  |
|--------------|--|
| Wattage      | 7W   |
| IP Rating    | IP65   |
| IK Rating    | IK08   |
| Material     | High corrosion resistance die-cast copper-free aluminum body and fixing arms |
| Coating      | Polyester powder coating with phosphocromating pre-finish                    |
| Light source | NR. 10 x CREE "XH-G" LED   |
| Screws       | Stainless steel  |
| Transformer  | Electronic power supply Integral 120VAC                                      |
| Gasket       | Silicone rubber  |
| Gross weight | 3.3 lbs  |

| light source*            | light beam options        | lumen output (lm) | lumin. efficacy (lm/w) |
|--------------------------|---------------------------|-------------------|------------------------|
| <b>3000°K warm-white</b> |                           |                   |                        |
| mid-power led            | mono directional diffused | 330               | 47.14                  |

\* Other light colors available on request: Neutral-white

## Finish color options:

 Textured Gray  
RAL 9006

 Anthracite Gray  
RAL 7016

 Matte Black  
(on request)

