

## Technical features

IP65 IK08




402402P

# HORIZON MINI 02

Designed by  
PAOLO VILLA

Applique of rectangular shape for outdoor installation on a facade/wall, with double light emission (up/down). Phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered frosted safety glass, molded silicone gasket and stainless steel screws. Integral 120VAC 50-60Hz, with 20 mid-power CREE XH-G LED. IP65 rating.



## Technical data

Wattage	14W
IP Rating	IP65
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminum body and fixing arms
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 20 x CREE "XH-G" LED
Screws	Stainless steel
Transformer	Electronic power supply 120VAC 50-60Hz Integral
Gasket	Silicone rubber
Gross weight	2.2 lbs



light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
mid-power led	bi-directional diffused	650	46.43

\* Other light colors available on request: Neutral-white

## Finish color options:

 Textured Gray  
RAL 9006

 Anthracite Gray  
RAL 7016

 Matte Black  
(on request)

