

## Technical features


IP67 IK10



202010P

## HYDROQUADRO MAXI PRO

Square ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminum body and stainless steel AISI 304 frame, tempered safety glass, molded silicone gasket. Built-in LED driver 120VAC 50-60Hz, with 16 CREE XP-L LED. IP67 rating.



## Technical data

Wattage	44W
IP Rating	IP67
IK Rating	IK10
Material	High corrosion resistance die-cast copper-free aluminum body
Trim	Stainless steel AISI 304
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 16 CREE "XP-L" LED
Screws	Stainless steel
Transformer	Electronic power supply 120VAC 50-60Hz built-in
Static weight	Max 11,000 lbs resistance
Gasket	Silicone rubber
Glass	Tempered
Cable gland	Double M20
Adjustable	+/- 15 degrees
Power cable	3.28' neoprene power cable included
Gross weight	12.6 lbs
Included	Polypropilene recessing box included



light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
high-power led	10°	3,920	89.10
high-power led	30°	3,720	84.55
high-power led	45°	3,540	80.45

\* Other light colors available on request: Neutral-white

### Finish color options:

 Stainless Steel