The Magic Of Light.

i-lantern

design by Landa R&D





i-lantern

I-Lantern is characterized by a strong personality, a direction of light with a diffuse light beam and a 10W powerful heart, perfect for wall applications. An aesthetic fusion lives in parallel with a minimal design in order to be declined in many possible outdoor installations. Composed of a structural framework in extruded aluminum, I-Lantern is a luminaire with the possibility to be managed and dimmed via Bluetooth on request. I-Lantern lights the outdoors of private spaces and beyond.

I-LANTERN | BOLLARD
I-LANTERN | POLE
I-LANTERN | GARDEN LAMP





i-lantern

DIFFUSE




TECHNICAL SPECIFICATIONS

IK rating

LED 10W Source lamp 12.5W Total wattage 120-277VAC, 50-60 Hz 0-10V Dimming 3000K Luminous flux 700 lm (1360 lm*) *Source flux Luminous efficacy 56 lm/W 3 McADAM steps Beam diffuse > 90 CRI Life time L70 > 50,000 h Ta 40°C IP rating IP65

IK08

DIFFUSE



-13.1' -9.8' -6.6' -3.3' 0 3.3' 6.6' 9.8' 13.1'

".6.1 ".9.1 ".9.1

MATERIALS

Body Die-cast aluminum EN47100
and extruded aluminum EN-AW6060

Diffuser Opal polycarbonate

Finishing Polyester powder paint

ORDER CODE

LN 7 0 PAR D H B B Z _

- Finishing

L	Graphite	
٧	Oxide	•
U	White	
G	Black	•

Example

LN 7 0 PAR D H B B Z L



